

STATE MACHINE PRODUCTS INC (OUT OF BUSINESS) -- VV-L-820 LUBRICATING OIL --  
7360-00-187-4757

=====  
Product Identification  
=====

Product ID:VV-L-820 LUBRICATING OIL

MSDS Date:09/17/1992

FSC:7360

NIIN:00-187-4757

MSDS Number: BNTBD

=== Responsible Party ===

Company Name:STATE MACHINE PRODUCTS INC (OUT OF BUSINESS)

Address:22 WARSAW RD

City:DRY RIDGE

State:KY

ZIP:41035-9757

Country:US

Info Phone Num

:804-279-4371 (DGSC-HMIS)

Preparer's Name:HMIS TECHNICIAN

CAGE:18789

=== Contractor Identification ===

Company Name:STATE MACHINE PRODUCTS INC.

Address:22 WARSAW RD

Box:City:DRY RIDGE

State:KY

ZIP:41035-9757

Country:US

Phone:606-823-5311

CAGE:18789

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM BASE OIL (LUBRICATING OIL)

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:

YES Skin: YES Ingestion: YES

Health Hazards Acute and Chronic: ACUTE: MILD IRRITATION OF EYES, SKIN OR RESPIRATORY TRACT. CHRONIC: IRRITATION OR DERMATITIS.

Effects of Overexposure: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN OR EYE IRRITATION.

Medical Cond Aggravated by Exposure: NO DATA AVAILABLE.

=====  
===== First Aid Measures =====

First Aid: SKIN: WASH THOROUGHLY WITH SOAP & WARM WATER EYE: -FLUSH WITH WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES.

=====  
===== Fire Fighting Measures =====

Flash Point Method: COC

Flash Point: 320F/160C

Lower Limits: 1.0

Upper Limits: 6.0

Extinguishing Media: FOAM, DRY CHEMICAL, CO<sub>2</sub>, OR WATER FOG OR SPRAY

Fire Fighting Procedures: KEEP EXPOSED CONTAINERS COOL WITH WATER SPRAY

Unusual Fire/Explosion Hazard: DO NOT MIX OR STORE WITH STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.

=====  
===== Accidental Release Measures =====

Spill Release Pro

cedures: RECOVER FREE LIQUID ADD ABSORBENT LIKE SAND OR EARTH TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS & WATERWAYS. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS, WATERWAYS OR EXTENSIVE LAND AREA.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE.

DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions: AVOID BREATHING OIL MIST. REMOVE OIL SOAKED CLOTHING

AND LAUNDRY PRIOR TO REUSE. DISCARD OIL SOAKED SHOES. WASH SKIN THOROUGHLY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE SHOULD BE NEEDED. USE AIR SUPPLIED RESPIRATOR IN CONFINED SPACES.

Ventilation: MECH(GEN) OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICAIN SINCE MFR IS OUT OF BUSINESS. WAS  
GENERATED FROM SIMILAR MATERIAL FROM ANOTHER MFR AND SPEC SHEET.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:504F/282C

Vapor Pres:11.0

Spec Gravity:0.9

Evaporation Rate & Reference: