

GENERAL ELECTRIC CO. SILICONE PRODUCT DIV. -- TBS 758A -- 8030-01-026-4058

=====
Product Identification
=====

Product ID:TBS 758A

MSDS Date:12/20/1989

FSC:8030

NIIN:01-026-4058

Kit Part:Y

MSDS Number: BNTPC

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO. SILICONE PRODUCT DIV.

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone Num:518-237-3330

Prep

Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

=====
Composition/Information on Ingredients
=====

Ingredient Name:SILICONE THERMAL BARRIER (NONHAZARDOUS INGREDIENT)

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN- PLANT EXPERIENCE HAS SHOWN THAT
SKIN HAZARD IS NOT APPLICABLE IN THIS FORM. EYE- MAY CAUSE MILD EYE
IRRITATION.

=====
First Aid Measures
=====

First Aid:SKIN- WASH WITH SOAP AND WATER. EYES- IN CASE OF CONTACT,
IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES
AND GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

=====
Fire
Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:400F,204C
Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL
AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH
DETERGENT & WATER TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE
EQUIPMENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT SECTION.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT WITH EYES.

=====
Exposure Controls/Personal Protection
=====

Protective Gloves:CLOTH GLOVES
Other Protective Equipment:EYEWASH STATIONS.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:>500F,>260C
Vapor Pres:NEGL. MMHG
Vapor Density:NEGL.
Spec Gravity:1.32
Evaporation Rate & Reference: