

INDUSTRIAL POLYCHEMICAL SERVICE -- WELD-ON 1707 FOR ABS PLASTIC -- 8040-01-235-2642
===== Product Identification =====

Product ID:WELD-ON 1707 FOR ABS PLASTIC
MSDS Date:01/01/1987
FSC:8040
NIIN:01-235-2642
MSDS Number: BNTRN
=== Responsible Party ===
Company Name:INDUSTRIAL POLYCHEMICAL SERVICE
Address:17109 S MAIN
Box:379
City:GARDENA
State:CA
ZIP:90248
Country:US
Emergency Phone Num:213-321-651
5
CAGE:17510
=== Contractor Identification ===
Company Name:IPS CORPORATION
Address:17109 S. MAIN ST.,
Box:379
City:GARDENA
State:CA
ZIP:90248
Country:US
Phone:310-898-3300
CAGE:17510

===== Composition/Information on Ingredients =====

Ingred Name:ACRYLONITRILE BUTADIENE STYRENE RESIN (ABS)
CAS:9003-56-9
Fraction by Wt: 15-25%
Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL ETHYL KETONE (MEK)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 75-85%
Other REC Limits:NONE SPECIF

IED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:SEVERE OVEREXPOSURE MAY RESULT IN NAUSEA,
DIZZINESS, HEADACHE. CAN CAUSE NARCOSIS, IRRITATION OF EYES AND
NASAL PASSAGES. MAY IRRITATE SKIN. NORMAL DEFATTING EFFECT OF
SOLVENTS ON TISSUE.

===== First Aid Measures =====

First Aid:INHAL: IF OVERCOME BY VAPORS: REMOVE TO FRESH AIR, IF
BREATHING STOPPED-GIVE ARTIFICIAL RESPIRATION (PREFER MOUTH TO
MOUTH). IF BREATHING DIFFICULT-GIVE OXYGEN. CALL DR. EYE: FLUSH
W/PLENTY OF WATER F OR 15 MINS. CALL DR. SKIN: REMOVE CONTAMINATED
CLOTHING/SHOES. WASH WITH WATER FOR 15 MINS-CALL DR. INGEST: GIVE 1
OR 2 GLASSES OF WATER OR MILK AND INDUCE VOMITING. CALL DR
IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:21.0F,-6.1C
Lower Limits:1.8
Upper Limits:10.0
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM - ANSUL "PURPLE
K" - NATIONAL AER-O-FOAM, WATER FOG.
Fire Fighting Procedures:EVAC AREA/STAY UPWIND. CLSE/CONFND QTRS REQ
SCBA; POSITIVE PRESS HOSE/AIRLINE MASKS. USE WTR SPRAY: COOL
CNTNRS/FLUSH SPILLS FROM SOURCE OF IGNIT/DISPERSE VAPOR
Unusual Fire/Explosion Hazard:FIRE HAZARD BECAUSE OF LOW FLASH
POINT
AND HIGH VOLATILITY. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO
SOURCE OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL IGNIT SOURCES. AVOID BREATH OF
VAPORS. KEEP LIQ OUT OF EYES. FLUSH W/LG VOL OF WTR. CONTAIN LIQ
W/SAND OR EARTH. ABSORB W/SAND OR NONFLAMMABLE ABSORB MATL &
TRANFER INTO STEEL DRUMS FOR RECOV ERY OR DISPOSAL. PREVENT LIQ
FROM ENTERING DRAINS.

===== Handling and

Storage =====

Handling and Storage Precautions:STORE IN SHADE BETWN 40F & 110F. KEEP FROM: HEAT/SPARKS/OPEN FLAME & OTHER SOURCES OF IGNITION. AVOID PROLONGED BREATHING OF VAPOR. USE W/ADEQ VENT.

Other Precautions:FOLLOW ALL PRECAUTIONARY INFORMATION GIVEN ON THE CONTAINER LABEL, PRODUCT BULLETIN & OUT CEMENTING LITERATURE. ALL HANDLING EQUIPMENT SHOULD BE ELECTRICALLY GROUNDED.

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:NONE REQUIRED WITH ADEQUATE VENTILATION. USE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS FOR CONFINED AREAS, E.G., MINE SAFETY APPLIANCE CAT. #459433.

Ventilation:PROVIDE ADEQUATE VENTILATION. VAPOR CONCENTRATION MUST BE KEPT WELL BELOW TLV.

Protective Gloves:RUBBER OR PVA

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:IMPERVIOUS APRON (IF NEEDED)

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B

.P. Text:175.2

Vapor Pres:71.2 @ 23C

Vapor Density:2.5

Spec Gravity:0.870 + 0.006

Evaporation Rate & Reference:(BUAC = 1) APPROX 5.7

Solubility in Water:27.1 (SOLVENT)

Appearance and Odor:MILKY, TRANSLUCENT, MEDIUM SYRUPY LIQUID. KETONE ODOR.

Percent Volatiles by Volume:85-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

CAUSTICS, AMMONIA, INORGANIC ACIDS, CHLORINATED COMPOUNDS, STRONG OXIDIZERS AND ISOCYNATES.

Stabil

ity Condition to Avoid:KEEP FROM: HEAT/SPARKS/OPEN FLAME/OTHER SOURCE OF IGNITION. THIS LIQ IS VERY STABLE AT NORMAL AMBIENT TEMPERATURES.

Hazardous Decomposition Products:DENSE SMOKE CONTAINING CARBON MONOXIDE, CARBON DIOXIDE AND HYDROGEN CYANIDE.

Conditions to Avoid Polymerization:KEEP AWAY FORM HEAT, SPARKS, OPEN FLAME AND OTHER SOURCES OF IGNITION.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW LOCAL, STATE AND FEDERAL REGULATIONS.

CONSULT DISPOSAL EXPERT. CAN BE DISPOSED OF BY INCINERATION. EXCESSIVE QUANTITIES SHOULD NOT BE PERMITTED TO ENTER DRAINS.

HAZARDOUS WASTE CODE: U159

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person

utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.