

ROYAL LUBRICANTS COMPANY INC -- ROYCO 28 -- 9150-01-304-6603

=====
Product Identification
=====

Product ID:ROYCO 28

MSDS Date:11/01/1985

FSC:9150

NIIN:01-304-6603

MSDS Number: BNTTH

=== Responsible Party ===

Company Name:ROYAL LUBRICANTS COMPANY INC

Address:RIVER RD

Box:518

City:E HANOVER

State:NJ

ZIP:07936

Country:US

Info Phone Num:201-887-7410

Emergency Phone Num:201-887-7410;800-424-9300(CHEMT
REC)

CAGE:07950

=== Contractor Identification ===

Company Name:ROYAL LUBRICANTS COMPANY INC.

Address:215 MERRY LN

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Phone:973-887-7411/7410

CAGE:07950

=====
Composition/Information on Ingredients
=====

Ingred Name:SYNTHETIC HYDROCARBON BASE STOCK; (SYNTHETIC HYDROCARBON)
Fraction by Wt: >73%

Ingred Name:NITROUS ACID, SODIUM SALT; (SODIUM NITRITE) (INCORPORATED
INTO CLAY)

CAS:7632-00-0

RTECS #:RA1225000

Fraction by Wt:

254C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL POWDER, OR FOAM EXTINGUISHER. DO NOT USE WATER JET.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . COOL FIRE EXPOSED CONTAINERS, SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. CLEAN AREA WITH APPROPRIATE CLEANER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE W/ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

Other Precautions:MINIMIZE SKIN CONTACT. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES THAT CANNOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT ORDINARILY REQUIRED. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:OIL RESISTANT GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:CLOTHING AS NEEDED TO MINIMIZE SKIN CONTACT.

Work Hygienic Practices:WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

HAZ DECOMP PRODS:&

GASES WILL EVOLVE WHEN MATL UNDERGOES PYROLYSIS/COMBUST. CO & UNIDENTIFIED ORG CMPDS MAY BE FORMED UPON COMBUST. EFTS OF OVEREXP:BEEN FOUND THAT PURE SODIUM NITRATE, IF INGESTED, MAY CAUSE NAUS, VOMIT, ABDOMINAL PAINS, HYPOTENSION, MUSCULAR WEAKNESS, COLLAPSE, CONVUL, CYANOSIS, UNCON & RESP PARALYSIS.

===== Physical/Chemical Properties =====

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER BUTTERY CLAY THICKENED GREASE W/SLIGHT ODOR.

===

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HEAT, OPEN FLAME.

Hazardous Decomposition Products: THERM DECOMP PRODS ARE HIGHLY
DEPENDENT ON COMBUST CNDTNS. A COMPLEX MIXTURE OF AIRBORNE SOLID,
LIQ PARTICULATES(SUPDAT)

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN APPROPRIATE DISPOSAL FACILITY IN

COMPLIANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.