

AM GENERAL CORP; SERVICE PARTS LOGISTICS OPNS/SPLO -- MB73-20002 -- 6140-01-117-9510  
===== Product Identification =====

Product ID:MB73-20002

MSDS Date:10/09/1992

FSC:6140

NIIN:01-117-9510

MSDS Number: BNWSG

=== Responsible Party ===

Company Name:AM GENERAL CORP; SERVICE PARTS LOGISTICS OPNS/SPLO

Address:408 S BYRKIT AVE

Box:728

City:MISHAWAKA

State:IN

ZIP:46546-0728

Country:US

Info Phone Num:219-

258-6669

Emergency Phone Num:219-258-6669

Preparer's Name:HMIS TECHNICIAN

CAGE:34623

=== Contractor Identification ===

Company Name:AM GENERAL CORP; SERVICE PARTS LOGISTICS OPNS/SPLO

Address:408 S BYRKIT AVE

Box:728

City:MISHAWAKA

State:IN

ZIP:46546-0728

Country:US

Phone:219-258-6669

CAGE:34623

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TL

V:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 2140 MG/KG (H2SO4)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acu

te and Chronic:ACUTE: MAY CAUSE IRRITATION OF

RESPIRATORY TRACT, EYES, SKIN OR GI TRACT. MAY CAUSE BURNS OF SKIN,  
EYES, OR GI TRACT. MAY CAUSE CORNEAL DAMAGE OR BLINDNESS. CHRONIC:  
TOOTH EROSION, INFLAMMATION OF NOS E, THROAT AND BRONCHIAL TUBES.

Explanation of Carcinogenicity:THE ELECTROLYTE IS NOT LISTED BY IARC,  
NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALATION: BURNING SENSATION IN NOSE, THROAT  
AND LUNGS, COUGHING, WHEEZING, SHORTNESS OF BREATH. EYES: REDNE  
SS,

TEARING, BLURRED VISION, BURNS, SEVERE PAIN. SKIN: SEVERE PAIN,  
BURNS, REDNESS, RASH, I TCHING. INGESTION: BURNS OF MOUTH, THROAT,  
AND ESOPHAGUS, SEVERE STOMACH PAIN, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS  
OR WITH A PRE-EXISTING DISEASE INVOLVING THE RESPIRATORY TRACT OR  
TEETH MAY BE AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH

AIR. RESUSCITATE IF NOT BREATHING.

GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER  
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET PROMPT MEDICAL ATTENTION.

SKIN :REMOVE CONTAMINATED CLOTHING. WASH WITHPLENTY OF WATER FOR 15  
MINUTES. GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING.

GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL  
ATTENTION.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:USE DRY CHEMI

CAL, CARBON DIOXIDE, FOAM, HALOGEN.

Fire Fighting Procedures:USE OF WATER IN EXTINGUISHING BURNING

BATTERIES MAY CAUSE SPATTERING DUE TO THE PRESENCE OF MOLTEN LEAD.  
WEAR SCBA AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:AFTER ELECTROLYTE IS ADDED AND BATTERY IS  
BEING CHARGED, HYDROGEN GAS IS PRODUCED. BATTERY MAY EXPLODE IF  
HYDROGEN GAS TRAPPED INSIDE THE CASE SHOULD IGNITE.

===== Accidental Release Measures =====

Spill Release Procedures

:SHOULD A BATTERY BREAK OPEN, ISOLATE AREA.

ELECTROLYTE SHOULD BE ABSORBED WITH A NON-ORGANIC TYPE ABSORBENT  
SUCH AS DRY SAND OR EARTH. AVOID DILUTION WITH WATER. LEAD SPILLED  
FROM THE BATTERY SHOULD B E VACUUMED, DO NOT SWEEP OR USE  
COMPRESSED AIR.

Neutralizing Agent:USE SODA ASH OR BAKING SODA TO NEUTRALIZE THE  
ELECTROLYTE.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID THE USE OF UNINSULATED TOOLS. IF  
THEY A

RE REQUIRED, TAKE CARE NOT TO ELECTRICALLY SHORT THE  
TERMINALS. REMOVE METAL JEWELRY BEFORE SERVICING.

Other Precautions:UNDER NORMAL CONDITIONS OF USE, EXPOSURE TO LEAD OR  
LEAD CONTAINING COMPOUNDS DOES NOT OCCUR. SHOULD A BATTERY BREAK  
OPEN AND A LEAD SPILL OCCUR, PRECAUTIONS SHOULD BE TAKEN TO PREVENT  
LEAD DUST FROM BECOMING AIR BORNE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNDER NORMAL CONDITIONS OF USE, RESPIRATORY  
P

ROTECTION IS NOT REQUIRED. HOWEVER, IF CONDITIONS ARISE THAT  
REQUIRE THEIR USE, USE ONLY NIOSH/MSHA RESPIRATORS APPROVED FOR  
DUST, FUME AND MIST.

Ventilation:BATTERY CHARGING AREAS MUST BE ADEQUATELY VENTILATED TO  
PREVENT HAZARDOUS CONCENTRATIONS OF FLAMMABLE GAS OR ACID MIST.

Protective Gloves:RUBBER GLOVES APPROVED FOR SULFURIC ACID

Eye Protection:CHEMICAL SPLASH GOGGLES AND FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.  
INDUSTRIAL-TYPE IMPERVIOUS WO

RK CLOTHING, BOOTS AND APRON AS  
REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN FOR TECHNICAL SUPPORT. MFR UNABLE TO  
GIVE MSDS IN REASONABLE AMOUNT OF TIME.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:203F,95C

Vapor Pres:10

Vapor Density:>1

Spec Gravity:1.23-1.35

pH:1

E

vaporation Rate & Reference: