

NILES CHEMICAL PAINT CO -- N-1207A EARTH YELLOW CAMO TYPE IV -- 8010-01-130-3346

=====
Product Identification
=====

Product ID:N-1207A EARTH YELLOW CAMO TYPE IV

MSDS Date:10/06/1991

FSC:8010

NIIN:01-130-3346

Kit Part:Y

MSDS Number: BNWSM

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT ST

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377 OR

219-236-5856

Emergency Phone Num:616-683-3377 OR 219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:PM ACETATE (VAPOR PRESSURE 3.7 MM HG @ 20C)

CAS:108-65-6

RTECS #:A18925000

Fraction by Wt: 17%

Other REC Limits:NONE SPECIFIED

Ingred Name:POLYESTER RESIN
Fraction by Wt: 16%
Other REC Limits:NONE SPECIFIED

Ingred Name:BUTYL ACETATE (VAPOR PRESSURE 10 MM HG @ 20C)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 9%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM
ACGIH TLV:150 PPM/200 PPM STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:GREEN PIGMENT (AS CR) (SARA 313)
CAS:1308-38-9
RTECS #:GB6475000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1.0 MG/M3
ACGIH TLV:0.5 MG/M3

Ingred Name:METHYL
ETHYL KETONE (SARA 313) (VAPOR PRESSURE 71.2 MM HG @
20C)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 7%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300 PPM STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPRIETARY INGREDIENTS
Fraction by Wt: BALANCE
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 4.38 LBS/GAL
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

Routes of Entry: Inha

lution: YES Skin: UNKNOWN Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: ACUTE: EYES: SEVERE IRRITATION,
LACRIMATION, REDNESS, BLURRED VISION. SKIN: REDNESS, IRRITATION,
DEFATTING OF THE SKIN LEADING TO DERMATITIS. BREATHING: NASAL &
RESPIRATORY IRRITATION, CNS DEPRESSION, ASPHYXIATION. SWALLOWING:
GASTROINTESTINAL IRRITATION. CHRONIC: HISTOLOGIC FIBROSIS OF LUNGS,
NARCOSIS, COMA.

Explanation of Carcinogenicity: NOT LISTED
BY NTP, IARC OR OSHA.

Effects of Overexposure: BREATHING: DIZZINESS, DROWSINESS, WEAKNESS,
FATIGUE, CONFUSION, NAUSEA, HEADACHE, VERTIGO, POSSIBLE
UNCONSCIOUSNESS. SWALLOWING: ABDOMINAL PAIN, NAUSEA, VOMITING,
DIARRHEA.

Medical Cond Aggravated by Exposure: NONE KNOWN. TARGET ORGANS:
RESPIRATORY SYSTEM, CNS, LUNGS, EYES, SKIN.

=====
===== First Aid Measures =====

First Aid: INHAL: MOVE TO FRESH AIR. IF BREATHING STOPPED, START ARTIF
RESP. GET MED
AID. SKIN: IMMEDIATE FLUSH W/WATER. IF MAT'L PENETRATES
CLOTHING, REMOVE CONTAM CLOTHING & FLUSH SKIN W/WATER. GET MED AID.
EYE: IMMEDIATE FLUSH W/LRG AMT WATER 15 MIN, LIFTING EYELIDS. GET MED
AID IMMEDIATE. SWALLOWING: DRINK 1-2 GLASSES WATER. DON'T INDUCE
VOMITING. CONSULT PHYSICIAN/POISON CONTROL CENTER IMMEDIATE. TREAT
SYMPTOMATICALLY.

=====
===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 20.0F, -6.7C

Lower Limits: 1.3

Upper Limits: 10.

0

Extinguishing Media: DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures: WEAR POS PRESS SCBA W/FULL FACEPIECE & FULL
PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO
PREVENT PRESS BLD UP & AUTO IGNIT/EXPLOS.

Unusual Fire/Explosion Hazard: VAPOR HEAVIER THAN AIR, TRAVEL TO IGNIT
SOURCE. ISOLATE FROM IGNIT SOURCE. CLSD CNTNR EXPLODE W/HEAT.
APPLICATION TO HOT SURFACES REQUIRE SPECIAL PRECAUTIONS.*

=====
===== Accidental Release Measures =====

Spill Release Procedures:NO IGNIT SOURCES. MINIMIZE BREATHING VAPORS.
AVOID SKIN CONTACT. SMALL: ABSORB W/INERT MAT'L(CLAY, SOIL, COMMERC
ABSORB). SHOVEL RECLAIMED LIQ & ABSORB INTO RECOVERY/SALVAGE DRUMS.
LRG:DIKE(NO FURTHER MOVEMENT)& RECLAIM INTO SALVAGE DRUMS/TANK
TRUCK.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE
AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED
WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN
EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. DO NOT WEAR CONTACT
LENSES WHEN WORKING WITH THIS MATERIAL.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROPRIATE (TC-23C-75) FITTED HALF-MASK OR
FULL FACEPIECE RSPRTR (NIOSH/MSHA) DURING & AFTER APPLICATION
UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS BELOW TL
V.

FOLLOW RESPIRATOR MFR DIR ECTIONS FOR USE.

Ventilation:PROVIDE SUFFICIENT VENTILATION (VOLUME/PATTERN) TO KEEP AIR
CONC BELOW TLV PEL. REMOVE DECOMP PROD. VENT VAPOR EMITTED.

Protective Gloves:CHEM RESISTANT GLOVES-NITRILE OR VITON

Eye Protection:CHEM GOGGLES/SAFETY GLASSES/FACE SHIELDS

Work Hygienic Practices:WASH ANY CONTAM CLOTHING OR CLOTH THAT BECOMES
WET BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING
RESTROOM.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 302F

Vapor Density:> AIR

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, ODOR OF SOLVENT.

Percent Volatiles by Volume:59.01

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS.

Stability Condition to Avoid:N/K *OVEREXPOS TO DECOMP

PROD MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT.
GET MEDICAL AID.

Hazardous Decomposition Products: CAN PRODUCE CARBON MONOXIDE AND/OR
CARBON DIOXIDE.

Conditions to Avoid Polymerization: HIGH TEMPERATURES, SHOCK FROM
DROPPING.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL REGULATIONS. EPA HAZARDOUS WASTE CODE: D001 (IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.