

APPLIED INDUSTRIAL MATERIALS CORP -- STEINEX - ALL GRADES -- 3680-01-230-1947

=====  
Product Identification  
=====

Product ID:STEINEX - ALL GRADES

MSDS Date:04/30/1992

FSC:3680

NIIN:01-230-1947

MSDS Number: BPBPZ

=== Responsible Party ===

Company Name:APPLIED INDUSTRIAL MATERIALS CORP

Address:ONE PARKWAY NORTH, SUITE 400

City:DEERFIELD

State:IL

ZIP:60015

Country:US

Info Phone Num:708-632-9065

Emerge

ncy Phone Num:708-940-8700

CAGE:0BEY7

=== Contractor Identification ===

Company Name:APPLIED INDUSTRIAL MATERIALS CORP

Address:ONE PARKWAY NORTH, SUITE 400

Box:City:DEERFIELD

State:IL

ZIP:60015

Country:US

Phone:708-940-8700

CAGE:0BEY7

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SODIUM SILICATE

CAS:1344-09-8

Fraction by Wt: >50%

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

=====  
Hazards Identification  
=====

Routes of

Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: DUSTS ARE IRRITATING TO  
MUCOUS MEMBRANES OF THE RESPIRATORY TRACT, MOUTH, THROAT, ESOPHAGUS  
& STOMACH. EYES/SKIN: IRRITATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:SHORT TERM: MAY CAUSE IRRITATION TO SKIN, EYES,  
NOSE AND THROAT; GASTROINTESTINAL TRACT UPSET. LONG TERM: LONG TERM  
EXPOSURE MAY CAUSE IRRITATION AND R  
EDNESS OF SKIN, AND EYES  
IRRITATION.  
Medical Cond Aggravated by Exposure:THERE IS NO KNOWN MEDICAL  
CONDITIONS ABNORMALLY AGGRAVATED BY EXPOSURE THIS PRODUCT.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST SEVERAL  
MINUTES. SEEK MED ATTN. SKIN: WASH WITH PLENTY OF WATER FOR AT  
LEAST 15 MINUTES. WASH AND REMOVE SOILED CLOTHING & FOOTWEAR BEFORE  
REUSE. SEEK MED ATTN. INHALATION: IF SYMPTOMS A  
RE PRESENT GET  
PERSON OUT OF AREA TO FRESH AIR. SEEK MED ATTN.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Extinguishing Media:CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:THIS PRODUCT IS NON-COMBUSTIBLE. USE WATER TO  
COOL EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:IF A MATERIAL IS SPILLED OR RELEASED, STEPS  
SHOULD BE TAKE TO  
CONTAIN LIQUIDS/PREVENT DISCHARGES TO STREAMS OR  
SEWER SYSTEMS. COVER WITH SODA ASH, REMOVE INTO A CONTAINER, MIX  
AND ADD WATER TO DILUTE. NEUTRALIZE WITH ACID. MAY BE DRAINED  
W/PLENTY WTR  
Neutralizing Agent:SODIUM CARBONATE AND DILUTE ACETIC ACID.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY LOCATION. PROTECT  
FROM FREEZING.  
Other Precautions:NONE

=====  
Exposure Controls/Personal Protection  
=====

=====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR FOLLOWING MANUFACTURER'S RECOMMENDATIONS WHERE MISTS OR SPRAY MAY BE GENERATED.

Ventilation:PROVIDE LOCAL EXHAUST VENITLATION WHERE MISTS OR SPRAY MAY BE GENERATED, IF ENGINEERING CONTROLS ARE NOT FEASIBLE.

Protective Gloves:RUBBER

Eye Protection:FACE SHIELD, CHEMICAL GOGGLES

Other Protective Equipment:STANDARD WORK CLOTHING/SHOES. SHOWER & EYEWASH FACILITIES.

Work Hygienic Practices:REMOVE/WASH CONTAMINATED CLOTHING/FOOTWEAR BEFORE REUSE.

Supplemental Safety and Health

WT PER GAL: 12.0-13.0 LBS.

===== Physical/Chemical Properties =====

HCC:N1

Vapor Density:>AIR

Spec Gravity:1.5

pH: