View NSN Online: https://aerobasegroup.de/nsn/5330-00-252-0443

## FLEXITALLIC GASKET CO. -- ASBESTOS FILLED SPIRAL-WOUND GASKET -- 5330-00-252-0443

============= Product Identification ========================

Product ID: ASBESTOS FILLED SPIRAL-WOUND GASKET

MSDS Date:10/01/1991

FSC:5330

NIIN:00-252-0443

MSDS Number: BPBTL === Responsible Party ===

Company Name: FLEXITALLIC GASKET CO.

Address:8440 REMINGTON AVENUE

City:PENNSAUKEN

State:NJ ZIP:08110 Country:US

Info Phone Num:609-486-4400

Emer

gency Phone Num:609-486-4400

CAGE:72433

=== Contractor Identification ===

Company Name: FLEXITALLIC GASKET CO.INC

Address:8440 REMINGTON AVENUE

Box:286

City:PENNSAUKEN

State:NJ ZIP:08110 Country:US

Phone:609-486-4400

CAGE:72433

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:CI6478500

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

====== Hazards Identification

=======================================
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:BREATHINH OF ASBESTOS FIBERS IN SIGNIFICANT AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND CANCER.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS ASBESTOS WHICH IS A KNOWN CARCINOGEN.
======================================
Extinguishing Media:DETERMINE BY SURROUNDING MATERIALS, ASBESTOS NOT COMBUSTIBLE IN AIR.
======================================
Spill Release Procedures:VACUUM FINES AND DUST, CAREFULLY AVOIDING DUSTING. IF SWEEPING IS USED, CONTROL DUST BY WETTING AREA AND USED APPROPIATE DUST MASK.
============ Handling and Storage ==============
Handling and Storage Precautions:N/A, AS A FINISHED PRODUCT IN SPIRAL-WOUND GASKETS.
Other Precautions:SEE OTHER REGULATIONS FOR ASBESTOS HANDLING IN CFR 29, PART 1910, SUBPART 2, PARA. 1910.1001.
=====  Exposure Controls/Personal Protection =========
Respiratory Protection: USE MESA/MSA/OSHA RESPIRATOR IF DESIRED.  Ventilation: LOCAL EXHAUST: CONSULT LOCALLY APPLICABLE REGULATIONS FOR EMISSIONS.
Work Hygienic Practices:KEEP WORK AREA CLEAN OF ASBESTOS DUST. Supplemental Safety and Health NONE

======== Physical/Chemical Properties ==========

HCC:T7

Decomp Temp:Decomp Text:YN/AOWN
Spec Gravity:2.50
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT BLU

========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES
======== Disposal Considerations ============
Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

E WITH NO ODOR.