

BURKE INDUSTRIES -- PVC GRAPHITE TILES -- 9330-01-249-8426

=====
Product Identification
=====

Product ID:PVC GRAPHITE TILES

MSDS Date:11/19/1987

FSC:9330

NIIN:01-249-8426

MSDS Number: BPCDP

=== Responsible Party ===

Company Name: BURKE INDUSTRIES

Address: 2250 S 10TH

Box: 190

City: SAN JOSE

State: CA

ZIP: 95103

Country: US

Info Phone Num: 408-297-3500

Emergency Phone Num: 408-297-3500

CAGE: 96780

=== Contr

actor Identification ===

Company Name: BURKE INDUSTRIES

Address: 2250 S 10TH

Box: 190

City: SAN JOSE

State: CA

ZIP: 95103

Country: US

Phone: 408-297-3500

CAGE: 96780

=====
Composition/Information on Ingredients
=====

Ingred Name: GRAPHITE, NATURAL

CAS: 7782-42-5

RTECS #: MD9659600

Fraction by Wt: 46%

Other REC Limits: NONE SPECIFIED BY M.

OSHA PEL: 15 MPPCF RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9293

Ingred Name: VINYL ACETATE (SARA III)

CAS: 108-05-4

RTECS #: AK0875000

Fraction by Wt: TRACE

Other

REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15,A3 STEL;93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VINYL CHLORIDE MONOMER
Fraction by Wt: TRACE
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED OR REPEATED
BREATHING OF DUST CAN CAUSE PNEUMON
IOSIS.
Explanation of Carcinogenicity:VINYL CHLORIDE IS A CANCER SUSPECT
AGENT.
Effects of Overexposure:INHALATION: IF DUST FROM PRODUCT IS PRESENT,
BREATHING OF DUST MAY CAUSE COUGHING.
Medical Cond Aggravated by Exposure:PULMONARY DISEASES.

=====
===== First Aid Measures =====

First Aid:FIRST AID-INHALATION OF DUST, REMOVE TO FRESH AIR. EYE
CONTACT: FLUSH WITH WATER FOR 15 MINUTES. IF REDNESS OR IRRITATION
PERSIST CONTACT A DOCTOR. SKIN:WASH WI
TH SOAP AND WATER. INGESTION:
CONSULT A DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:ALCOHOL FOAM, DRY CHEMICALS, CARBON DIOXIDE.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROTECTIVE CLOTHING
AND SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:MAY EMIT TOXIC FUMES AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PICK UP TILES FOR REU

SE AND VACUUM OR SWEEP UP
DUST. WEAR DUST MASK.

=====
Handling and Storage
=====

Handling and Storage Precautions:PREVENT DUST ESCAPE INTO AIR. DON'T
BREATHE DUST.

Other Precautions:GRAPHITE DUST IS ELECTRICALLY CONDUCTIVE. DUST
ACCUMULATIONS CAN CAUSE SHORT CIRCUITS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH-APPROVED
RESPIRATOR UNDDER DUSTY CONDITIONS.

Ventilatio

n:NONE

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:FOLLOW GOOD HOUSEKEEPING PROCEDURES.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:N1

Spec Gravity:1.65

Solubility in Water:INSLUBLE

Appearance and Odor:BLACK, RIGID HOMOGENOUS FLUXED 12X12 TILES,
ODORLESS

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decompo

sition Products:CO, CO2

=====
Disposal Considerations
=====

Waste Disposal Methods:BURY IN LANDFILL IN ACCORDANCE W/FEDERAL, STATE,
& LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for i

ts use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.