

ASHLAND CHEMICAL CO DIV OF ASHLAND OIL INC -- SOLVENT 140-66 -- 6850-00-110-4498

===== Product Identification =====

Product ID:SOLVENT 140-66

MSDS Date:08/24/1989

FSC:6850

NIIN:00-110-4498

MSDS Number: BPFPN

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL CO DIV OF ASHLAND OIL INC

Address:1745 COTTAGE ST

City:ASHLAND

State:OH

ZIP:44805-1237

Country:US

Info Phone Num:614-790-3333

Emergency

Phone Num:606-324-1133

CAGE:33872

=== Contractor Identification ===

Company Name:ADVANCE PROCESS SUPPLY CO.

Address:400 NORTH NOBLE STREET

Box:City:CHICAGO

State:IL

ZIP:60622-6383

Country:US

Phone:312-942-8504

CAGE:29431

Company Name:ASHLAND CHEMICAL CO DIV OF ASHLAND OIL INC

Address:1745 COTTAGE ST

Box:City:ASHLAND

State:OH

ZIP:44805-1237

Country:US

Phone:419-289-9588

CAGE:33872

Company Name:GATOR SALES INC

Address:2719 PHILLIPS HWY

Box:City:JACKSONVILLE

State:FL

ZIP:32207

Country:US

Phone:904

-399-0901
CAGE:0A5V1

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC
CAS:64742-88-7
Fraction by Wt: 100.0%
Other REC Limits:500 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: CAUSES IRRITATION. SKIN:CAUSES
IRRITATION. MAY CAUSE AN ALLERGIC
SKIN REACTION. INGESTION: MAY BE
HARMFUL IF SWALLOWED. INHALATION: LOW HAZARD FOR RECOMMENDED
HANDLING.
Effects of Overexposure:EYES: CAUSES IRRITATION. SKIN:CAUSES
IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. ON PROLONGED
AND/OR REPEATED CONTACT MAY CAUSE DEFATTING, DERMATITIS. INGESTION:
MAY BE HARMFUL IF SWALLOWED. INHA LATION: EXCESSIVE INHALATION OF
VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION.
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH IMPAIRED PU
MONARY
FUNCTION OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY IRRITANTS
CONTAINED IN THE SOLVENT.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER BY LIFTING UPPER &
LOWER LIDS OCCASIONALLY-GET MEDICAL ATTN; SKIN: THOROUGHLY WASH
EXPOSED AREA WITH SOAP & WATER-REMOVE CONTAMINATED CLOTHING;
INHALATION: REMO VE TO FRESH AIR-ADMINISTER OXYGEN OR GIVE CPR-GET
MEDICAL ATTN PROMPTLY. INGESTION: DO NOT INDUCE
VOMITING. GET
MEDICAL ASSISTANCE IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:140F/60C
Lower Limits:1.0
Upper Limits:6.0%
Extinguishing Media:REGULAR FOAM OR DRY CHEMICAL OR CARBON DIOXIDE
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS WITH FULL
FACEPIECE IN PRESSURE DEMAND MODE.
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR MAY TRAVEL ALONG
GROUND & BE IGNITED BY HEAT, PILOT LIGHTS, OTHER

FLAMES, ETC.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL:ABSORB LIQ. ON VERMICULITE,FLOOR ABSORBENT,ETC. & TRANSFER TO HOOD; LARGE SPILL:ELIMINATE ALL IGNITION SOURCES, WEAR PROTECTIVE CLOTHING, STOP SPILL @ SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS MAY BE HAZARDOUS WHEN

EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES,ALL HAZARD PRECAUTIONS ON MSDS MUST BE OBSERVED.

Other Precautions:DO NOT USE NEAR HEAT, DO NOT WELD EMPTY CONTAINERS AS THEY MAY CONTAIN RESIDUAL LIQUID/VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MESA APPRVD SELF-CNTD BRTHNG APPAR.W/FULL FACEPIECE,IF TLV>EXD

Ventilation:GEN.MECHANICAL/LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV

Protective Gloves:BUNA-N

Ey

e Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:AS NEEDED TO PREVENT REPEATED/PROLONGED SKIN CONTACT

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

MSDS FROM ASHLAND CHEM CO.,DATED: 12/08/86 IS SUPECEDED BY MSDS OF 24 AUGUST 89; SPEC REF: P-D-680, TYPE II.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:35

5F/179.4C

Vapor Pres: