

MANSFILED OIL CO OF GAINESVILLE INC -- MID-GRADE GASOLINE -- 9130-00-148-7103

=====
Product Identification
=====

Product ID:MID-GRADE GASOLINE

MSDS Date:12/19/1986

FSC:9130

NIIN:00-148-7103

MSDS Number: BPFQN

=== Responsible Party ===

Company Name:MANSFILED OIL CO OF GAINESVILLE INC

Address:1025 AIRPORT PKY SW

City:GAINESVILLE

State:GA

ZIP:30505-0198

Country:US

Info Phone Num:404-532-7571

Emergen

cy Phone Num:404-532-7571

CAGE:2Y744

=== Contractor Identification ===

Company Name:MANSFILED OIL CO OF GAINESVILLE INC

Address:1025 AIRPORT PKY SW

Box:City:GAINESVILLE

State:GA

ZIP:30505-0198

Country:US

Phone:404-532-7571

CAGE:2Y744

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: < 25% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT

Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: < 20% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)

CAS:1634-04-4

RTECS #:KN5250000

Fraction by Wt: < 10% %

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fractio

n by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1PPM/5STEL;1910.1028

ACGIH TLV:10 PPM; A2; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:CYCLOHEXANE (SARA III)

CAS:110-82-7

RTECS #:GU6300000

Fraction by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM, 9

293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-3

RTECS #:QJ0525000

Fraction by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

=====

===== Hazards Identification =====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:EYE IRRITATION, PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION, PULMONARY EDEMA, BRONCHITIS, PNEUMONITIS.

Explanation of Carcinogenicity:PRODUCT MAY CONTAIN UP TO 4.9% BENZENE WHICH IS

CLASSIFIED AS CARCINOGENIC TO HUMANS.

Effects of Overexposure:EYE IRRITATION, SKIN DEFATTING/DRYING, HEADACHE, DIZZINESS, LOSS OF APPETITE, WEAKNESS, LOSS OF COORDINATION, CONVULSIONS, DELIRIUM, HALLUCINATIONS, NUMBNESS IN THE EXTREMITIES, LOSS OF DEEP TENDON REFLEXES.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES. IF IRRITATION

N PERSISTS, CONTACT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. SEE DOCTOR IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. IF NEC ESSARY RESUSCITATE. CAL A PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS; ASPIRATION HAZARD. CALL A PHYSICIAN IMMEIDATELY.

===== Fire Fighting Measures =====

Flash Point: