

CHEVRON ENVIRONMENTAL HEALTH CENTER INC. -- HEATING FUEL NO 1 -- 9140-00-286-5296

=====
Product Identification
=====

Product ID:HEATING FUEL NO 1

MSDS Date:01/03/1992

FSC:9140

NIIN:00-286-5296

MSDS Number: BPFWJ

=== Responsible Party ===

Company Name:CHEVRON ENVIRONMENTAL HEALTH CENTER INC.

Address:15299 SAN PABLO AVE.

Box:4054

City:RICHMOND

State:CA

ZIP:94804

Country:US

Info Phone Num:415-233-37

37 OR 800-582-3835

Emergency Phone Num:415-233-3737 OR 800-457-2022

CAGE:0AHD1

=== Contractor Identification ===

Company Name:CHEVRON ENVIRONMENTAL HEALTH CENTER INC

Address:15299 SAN PABLO AVE

Box:4054

City:RICHMOND

State:CA

ZIP:94804

Country:US

Phone:800-582-3835

CAGE:0AHD1

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT/KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Other REC Limits:NONE RECOMMENDED

Ingred Name:KEROSENE/KEROSENE HYDROD

ESULFURIZED
CAS:64742-81-0
Other REC Limits:NONE RECOMMENDED

Ingred Name:DISTILLATES, HYDROSULFURIZED MIDDLE
CAS:64742-80-9
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:DISTILLATES,STREIGHT RUN MIDDLE
CAS:64741-44-2
RTECS #:LX3296000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:KEROSENE, HYDRODESULFURIZED
CAS:64742-81-0
Other REC Limits:NONE SPECIFIED

Ingred Name:LIGHT HYDROCARBON BLEN
D
CAS:64741-59-9
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 5ML/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-INHALED:IRRITATES RESPIRATORY
TRACT,HEADACHE,NAUSEA,DIZZINESS,LOSS OF APPETITE,WEAKNESS,LOSS OF
COORDINATION.EYES:IRRITATION.SKIN:PROLONGED/REPEATED CONTACT CAN
CAUSE PAIN,SW
ELLING,BLISTERING.IN GESTION:MAY IRRITATE DIGESTIVE
TRACT.ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.CHRONIC-SKIN
DISCOLORATION,BLISTERS.
Explanation of Carcinogenicity:THE NIOSH HAS RECOMMENDED THAT WHOLE
DIESEL EXHAUST BE REGARDED AS POTENTIALLY CAUSING CANCER.
Effects of Overexposure:INHALATION CAUSES IRRITATION OF RESPIRATORY
TRACT, HEADACHE, NAUSEA, DIZZINESS, LOSS OF APPETITE, WEAKNESS, AND
LOSS OF COORDINATION. IRRITATES EYE. PROLONGED OR REPEATED SKIN
CONTACT

CAN CAUSE PAIN, SWELLING, BLISTERING. INGESTION MAY IRRITATE DIGESTIVE TRACT. ASPIRATION INTO THE LUNG MAY CAUSE LUNG DAMAGE.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THIS MATERIAL.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL CARE IN ALL CASES.INHALATION:REMOVE TO FRESH AIR.PROVIDE CPR/OXYGEN IF NEEDED.EYE:FLUSH WITH WATER FOR 15 MINUTES KEEPING EYELID OPEN.SKIN:WASH WITH SOAP

&

WATER.INGESTION:DO NOT INDUCE VOMITING.ASPIRATION HAZARD.IF UNCONSCIOUS,DRINK MILK/WATER.CALL PHYSICIAN.IF SPONTANEOUS VOMITING OCCURS,KEEP HEAD LOWER THAN HIPS TO PREVENT PULMONARY ASPIRATION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:100F,38C MIN

Lower Limits:0.6

Upper Limits:4.7

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. A FORCED STREAM OF WATER COULD SCATTER FLAMES OF FIRE.

Fire F

ighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:MAY FORM WATER VAPOR, CARBON MONOXIDE AND CARBON DIOXIDE. WATER RUNOFF TO SEWER MAY CARRY COMBUSTIBLE FUELS & CREATE A FIRE/EXPLOSION. MORE FIRE HAZARD IF >85F.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCE OF HEAT,SPARKS,FLAME,FRIC TION &

ELECTRICITY,INCLUDING INTERNAL COMBUSTION ENGINE.USE EXPLOSION-PROOF EQUIPMENT TO CLEAN UP.DIKE SPILL.PREVENT LIQUID FROM ENTERING SEWERS,WATERWAYS/LOW AREAS.SOAK UP WITH SAWDUST,SAND,OIL DRY.SHOVEL/SWEEP

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL,DRY WELL-VENTILATED AREA IN CLOSED CONTAINER AWAY FROM HEAT,IGNITION SOURCES & OXIDIZERS.

Other Precautions:COMBUSTIBLE LIQUID. USE WITH A

DEQUATE VENTILATION.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. GROUND AND BOUND CONTAINERS TO PREVENT STATIC SPARKS. USE EXP LOSION-PROOF ELECTRICAL SERVICES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN SITUATION WHERE VAPOR CONCENTRATIONS MAY EXCEED THE RECOMMENDED EXPOSURE LIMITS, A NIOSH-APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED SUPPLIE

D-AIR RESPIRATOR FOR E MERGENCIES.

Ventilation:GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF LOCAL EXHAUST TO KEEP VAPOR BELOW RECOMMENDED EXPOSURE LIMITS

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION.BARRIER CREAMS SPECIFIC FOR PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTICAL.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PIN A SAME NSN. EMPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE TO HEAT, F LAME; THEY MAY EXPLODE. DO NOT USE PRESSURE TO EMPTY DRUM OR DRUM MAY RUPTURE WITH EXPLOSIVE FORCE.

=====
===== Physical/Chemical Properties =====

HCC:

F4

Boiling Pt:B.P. Text:400F,204C

Spec Gravity:0.85

Solubility in Water:INSOLUBLE

Appearance and Odor:PALE YELLOW LIQUID WITH MILD PETROLEUM ODOR

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS CHLORATES, NITRATES, PEROXIDES, ETC.

Stability Condition to Avoid:HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

=====

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MAY BE BURNED IN AN APPROVED INCINERATOR. TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.