

CRAWFORD LABORATORIES, INC. -- MIL-C-22750E EPOXY CLEAR M0-086, PART A --
8010-01-313-8702

===== Product Identification =====

Product ID:MIL-C-22750E EPOXY CLEAR M0-086, PART A

MSDS Date:03/03/1992

FSC:8010

NIIN:01-313-8702

Kit Part:Y

MSDS Number: BPGLB

=== Responsible Party ===

Company Name:CRAWFORD LABORATORIES, INC.

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Country:US

|

Info Phone Num:312-376-7132

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:DAVID SCHMETTERER

CAGE:DO165

=== Contractor Identification ===

Company Name:CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL

ZIP:60609

Phone:800-424-9300 CHEMTREC

CAGE:DO165

Company Name:CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL

ZIP:60609

Country:US

Phone:312-376-7132

CAGE:5V430

===== Composition/Information on Ingredients ==

=====

Ingred Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 71.2 MM HG)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN RESIN
CAS:25085-99-8
Fraction by Wt: 30%
Other REC Limits:NONE SPECIFIED

Ingred Name:TOLUENE (SARA III) (CONTAINS A TRACE OF BENZENE) (VAPOR
PRESSURE 38 MM HG)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 331 GPL
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:OVEREXPOSURE: ACUTE TOXICITY RESULTING
IN HEADACHE, DIZZINESS, NAUSEA AND LOSS OF CONSCIOUSNESS. SEVERE
EYE IRRITATION POSSIBLY RES
ULTING IN PERMANENT DAMAGE. IRRITATED
MUCOUS MEMBRANES. VOMITING DUE TO INGESTION. DEFATTING & DRYING OF
SKIN. SENSITIZATION AFTER REPEATED CONTACT. UNLIKELY THAT NORMAL
WORK OPERATIONS *

Explanation of Carcinogenicity:YOU SHOULD BE AWARE THAT THIS RESIN HAS
BEEN REPORTED TO CAUSE CANCER IN LABORATORY ANIMALS.

Effects of Overexposure:* WITH THIS RESIN COULD PRODUCE ATMOSPHERIC
CONCENTRATIONS APPROACHING OSHA LIMIT.

===== First Aid Measures =====

=====

First Aid:EYE: FLUSH W/LUKEWARM LOW PRESSURE WATER 15 MIN, LIFT EYELIDS. GET MED AID. INHAL: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT. GIVE ARTIF RESP IF NOT BREATHING. GET MED AID. KEEP WARM & COMFORTABLE. NEVER GIVE UNCONSCIOUS PERSON LIQS. INGEST: CALL DR IMMED. ONLY INDUCE VOMIT ON DR'S INSTRUCTS. IF VOMIT OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQ INTO LUNGS. NEVER GIVE **

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:22.0F,-5.6C
Lower Limits:1.2
Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL.
Fire Fighting Procedures:USE WATER TO KEEP EXPOSED CNTNRS COOL, & TO KEEP FLAMMABLE STRUCTURE WET. DON'T ENTER FIRE AREA W/O PROPER PROTECTION BECAUSE HAZARD DECOMP PROD MAY BE PRESENT.
Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVERHEATED.

===== Accidental Release Measures =====

Spill Release Procedures:WARNING - FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH AN ABSORBENT AND PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:HAZARD-FLAMM. KNOW DOT REGS BEFORE TRANSPORTING MAT'L. WARNING: HOT ORGANIC CHEMICAL VAPORS/MIST SUCEPTIBLE TO SPONTANEOUS COMBUST WHEN MIXED W/AIR.
Other Precautions:IGNIT MAY OCCUR AT TEMPS BELOW THOSE PUBLISHED IN LITERATURE (AUTOIGNIT/IGNIT TEMPS). IGNIT TEMPS DECREASE W/INCREASING VAPOR VOL & VAPOR/AIR CONTACT TIME INFLUENCED BY PRESSURE CHANGES. IGNIT MAY OCCUR AT TYPICAL ELEVATED TEMP PROCESS #

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IMPORTANT-MUST PROVIDE ADEQUATE VENTILATION TO MAINTAIN VAPOR CONCENTRATION BELOW ESTABLISHED TLV LIM

IT AS GIVEN

BY OSHA. IN MORE CONFINED AREAS NIOSH/MSHA APPROVED RESPIRATOR EQUIPPED W/ORGANIC VAPOR CARTRIDGE SHOULD BE WORN.

Ventilation:MUST PROVIDE ADEQUATE VENTILATION, SEE RESPIRATORY PROTECTION.

Protective Gloves:USE RUBBER GLOVES.

Eye Protection:WEAR SAFETY GOGGLES, FACE SHIELD.

Other Protective Equipment:HAVE EYE BATH AND SAFETY SHOWER AVAILABLE.

Work Hygienic Practices:N/K *** CLOTHING & SHOES. WASH W/SOAP & WATER.

DON'T REUSE CONTAM CLOTHING/SHOES. IF IRRITATION PERSI

STS, GET MED

AID.

Supplemental Safety and Health

CONDITIONS, ESPECIALLY IN PROCESS OPERATING UNDER VACUUM IF SUBJECTED TO SUDDEN INGRESS OF AIR/OUTSIDE PROCESS EQUIP OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPOR/MIST TO ATMOSPHERE OC CURS. EVALUATE ANY PROPOSED USE IN ELEVATED TEMP PROCESS TO ASSURE SAFE OPERATING CONDITIONS ESTABLISHED/MAINTAINED.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:174 TO 232F

Vapor Den

sity:> AIR.

Spec Gravity:1.03

Viscosity:>200 CENT

Evaporation Rate & Reference:3.42 X N-BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR LIQUID; SOLVENT ODOR.

Percent Volatiles by Volume:40.0

Corrosion Rate:NOT CORR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MAY BE INCOMPATIBLE WITH OXIDIZING AGENTS AND STRONG ALKALIES.

Stability Condition to Avoid:AVOID HEAT, SPARKS, OPEN FLAMES AND INCOMPATIBILITIES

Hazardous Decomposition Products:INCOMPLETE COMBUSTION FOR PRODUCTS LIKE THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE, AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY. EPA HZD#: D001, IGNITABLE. ** ANYTHING BY MOUTH TO UNCONSCIOUS PER SON. SKIN: FLUSH W/WATER WHILE REMOVINGC

ONTAM ***

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.