View NSN Online: https://aerobasegroup.de/nsn/2530-01-156-8190

NUTURN CORPORATION -- FRICTION MATERIAL, MG-16, 25, 26, 33 AND 38 -- 2530-01-156-8190

Product ID:FRICTION MATERIAL, MG-16, 25, 26, 33 AND 38

MSDS Date:01/01/1987

FSC:2530

NIIN:01-156-8190

MSDS Number: BPJKD === Responsible Party ===

Company Name: NUTURN CORPORATION

Address:570 METROPLEX DRIVE

City:NASHVILLE

State:TN ZIP:37211 Country:US

Info Phone Num:615-834-3800

Emergen

cy Phone Num:615-597-6700

CAGE:DO495

=== Contractor Identification ===

Company Name: NATURE MAID PRODUCTS

Address: HWY 78 BAMBERG COUNTY INDUSTRIAL PARK

Box:1047

City:BAMBERG

State:SC ZIP:29003 Country:US

Phone:803-245-5126

CAGE:NATUR

Company Name: NUTURN CORPORATION

Address:570 METROPLEX DRIVE

Box:City:NASHVILLE

State:TN ZIP:37211

Phone:615-597-6700

CAGE:DO495

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:CI6478500

Ot

her REC Limits: NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293 Ingred Name:TALC CAS:14801-96-6 Fraction by Wt: 600C/O2 Extinguishing Media: WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Fire Fighting Procedures: WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: NO EXPLOSION HAZARD. FLAMMABLE ONLY IN OXYGEN RICH ATMOSPHERE AND TEMPERATURES IN EXCESS OF 600C (1112F). =========== Accidental Release Measures =============== Spill Release Procedures: GRINDING, DRILLING, MILLING ETC. CAN RESULT IN THE RELEASE OF AIRBORNE DUST. WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED DUST RESPIRATOR. VACUUM OR WET SWEEP TO REMOVE SPILLS. TRANSFER TO APPROPRIATE CONTAINERS FOR DISPOSAL. DO NOT RAISE DUST. ============ Handling and Storage =========================== Handling and Storage Precautions: STORAGE- STORE IN COOL P LACE. AVOID GENERATING DUSTS. Other Precautions: MONITOR TO DETERMINE IF DUST OR FIBER IS RELEASED ABOVE PERMISSIBLE TIME WEIGHTED AVERAGES. CLEAN STORAGE AREAS OF DUSTS BY VACUUMING. USE EVERY PRECAUTION TO KEEP AIRBORNE DUSTS TO A MINIMUM. COMPLY WITH OSHA STANDARD 1910.1001. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NIOSH-APPROVED RESPIRATOR FOR DUSTS, IF TLV'S EXCEEDED. Ventilation:LOCAL EXHAUST FOR DUST EXPOSURES EXCEEDI NG TLV. Protective Gloves: RECOMMENDED

Eye Protection: RECOMMENDED FOR DUSTY CONDITIONS

Other Protective Equipment:LONG SLEEVE SHIRTS OR OTHER PROTECTIVE CLOTHING, EYE BATH FOUNTAIN, QUICK EMERGENCY SHOWER.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

======== Physical/Chemical Properties ============

HCC:N1

Spec Gravity: 1.4 - 2.4

Solubility in Water: INSOLUBLE

Appearance and Odor:REDDISH BROWN

## TO GREY BLACK - RESINOUS, OIL OR RUBBER ODOR

=======================================	Stability	and Reactivity	y Data	
---	-----------	----------------	--------	--

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:NONE KNOWN

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This infor

mation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.