

OCTAGON PROCESS INC. -- OCTOIL 90-2 -- 7360-00-187-4757

===== Product Identification =====

Product ID:OCTOIL 90-2

MSDS Date:03/09/1987

FSC:7360

NIIN:00-187-4757

MSDS Number: BPMCC

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945-9400

Emergency Phone Num:201-945-9400

Preparer's Name:IRIS CHAR

MS

CAGE:82925

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

Company Name:DRESSER ARGUS INC

Address:36 BRIDGE ST

Box:City:BROOKLYN

State:NY

ZIP:11201-1115

Country:US

Phone:718-643-1540

CAGE:84583

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====

= Composition/Information on Ingredients =====

Ingred Name:PROPRIETARY COMPONENT

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:TLV: 5 MG/M3 FOR OIL MIST.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD IRRITATION OR DERMATITIS. MINIMALLY IRRITATING TO EYES.

INHALATION OF VAPORS, GENERATED AT HIGH TEMPERATURES ONLY, OR OIL MIST MAY CAUSE MILD IRRITATION TO RESPIRATORY TRACT.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:IF INGESTED,  
DO NOT INDUCE VOMITING, CALL A PHYSICIAN. REMOVE  
CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP AND WATER. IN CASE OF  
CONTACT WITH EYES, FLUSH EYES WITH WATER UNTIL IRRITATION SUBSIDES.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:320F,160C

Autoignition Temp:Autoignition Temp Text:UNKNON

Lower Limits:1%

Upper Limits:7%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR  
FOG.

Fire Fighting Procedures:USE AIR

-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED  
AREAS.

Unusual Fire/Explosion Hazard:COOL FIRE-EXPOSED CONTAINERS WITH WATER  
SPRAY. DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL  
AREA. SHUT OFF IGNITION SOURCES. VENTILATE ENCLOSED SPACES. KEEP  
PETROLEUM PRODUCT OUT OF STREAMS & WATERWAYS. LARGE SPILLS CAN BE  
VACUUMED UP & PLACED INTO SALVAGE VESSELS

FOR SUBSEQUENT  
DISPOSAL/RECOVERY

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP CONTAINERS LOSED. KEEP AWAY FROM HEAT AND OPEN FLAMES. DO NOT STORE NEAR STRONG OXIDANTS.

Other Precautions:WASH HANDS AND FACE AFTER USE. LAUNDER CONTAMINATED CLOTHINMG BEFORE REUSE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NORMALLY NOT NEEDED. IF OIL MIST IS EXPECTED TO EXCEED TLV, USE NI

OSH APPROVED VAPOR RESPIRATOR.

Ventilation:LOCAL AND MECHANICAL(GENERAL) EXHAUST TO PROVIDE ADEQUATE VENTILATION.

Protective Gloves:NEOPRENE OR POLYVINYL ALCOHOL GLOVES

Eye Protection:GOGGLES

Other Protective Equipment:OIL-IMPERVIOUS APRON. SAFETY SHOES. EYE-WASH FOUNTAIN. SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====  
Phys  
ical/Chemical Properties  
=====

HCC:N1

Boiling Pt:B.P. Text:550-750F

Vapor Pres: