

MOBIL OIL CORP -- GARGOYLE ARCTIC OIL 300 -- 9150-01-023-4691

=====
Product Identification
=====

Product ID:GARGOYLE ARCTIC OIL 300

MSDS Date:09/06/1991

FSC:9150

NIIN:01-023-4691

MSDS Number: BPMJJ

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037

Country:US

Info Phone Num:800-662-4525;800-227-0707

Emergency Phone Num:609-737-4411;800-42

4-9300(CHEMTREC)

Preparer's Name:ENVIRON HLTH & SFTY DEPT

CAGE:1E969

=== Contractor Identification ===

Company Name:MOBIL OIL CORP

Address:530 EAST SWEDES FORD ROAD

Box:1031

City:VALLEY FORGE

State:PA

ZIP:19482

Country:US

Phone:703-849-3265

CAGE:1E969

Company Name:MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY

Address:PENNINGTON-ROCKY HILL RD

Box:City:PENNINGTON

State:NJ

ZIP:08534

Country:US

CAGE:0AHK0

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT R

EFINED HEAVY NAPHTHENIC DISTILLATE, PETROLEUM

CAS:64741-96-4

RTECS #:PY8040000

Fraction by Wt: 100%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:SUPP DATA:CHARACTERISTICS AT TIME OF DISPOSAL. DISPOSAL
MUST BE I/A/W LOCAL, STATE, AND FEDERAL REGULATIONS .

RTECS #:9999999ZZ

Ingred Name:ING 2:BE USED TO FLUSH SPILLS AWAY FROM EXPOS.PVNT RUNOFF
FROM FIRE CONTROL/DILUTION FROM ENTERING STREAMS, (ING 4)

RTECS #:9999999ZZ

Ingred Name:ING 3: SEWERS/DRINKING WATER SUPPLY.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SLIGHT SKIN IRRITATION.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH POTABLE WATER FOR A MINIMUM OF 15 MINUTES.
CALL MD . SKIN:WASH CONTACT AREAS WITH SOAP & WATER. INHAL:MOVE TO
FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTF RESP) . INGEST:GET MD.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>340F,>171C

Lower Limits:0.6%

Upper Limits:7%

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.

Fire Fighting Procedures:WEAR NIOSH/MSHA

APPROVED SCBA & FULL PROT

EQUIP . WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CNTNRS COOL. WATER SPRAY MAY (SUPDAT)

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPRPRIATE WASTE DISPOSAL FACILITY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handlin
g and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health

FIRE FIGHT PROC:BE USED TO FLUSH SPILLS AWAY FROM EXPOS. PVNT RUNOFF FROM FIRE CNTRL OR DILUTION FROM ENTERING STREAMS, SEWERS, OR DRINKING WATER SUPPLY. WASTE DISP METH:AT ANY GOVERNMENT APPRVD WASTE FACILITY. US

E OF THESE METHODS IS SUBJECT TO USER COMPLIANCE W/APPLIC LAWS/REGS & CONSIDERATION OF PROD (ING 2)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>500F,>260C

Vapor Pres: