

FLEXITALLIC GASKET CO -- ASBESTOS FILLED SPIRAL WOUND GASKET -- 5330-01-044-2328
===== Product Identification =====

Product ID:ASBESTOS FILLED SPIRAL WOUND GASKET

MSDS Date:07/09/1986

FSC:5330

NIIN:01-044-2328

MSDS Number: BPMJL

=== Responsible Party ===

Company Name:FLEXITALLIC GASKET CO

Address:6915 LAPORTE RD

City:DEER PARK

State:TX

ZIP:77536

Country:US

Info Phone Num:713-479-3491

Emergency Pho

ne Num:713-479-3491

CAGE:5N484

=== Contractor Identification ===

Company Name:FLEXITALLIC GASKET CO

Address:6915 LAPORTE RD

Box:City:DEER PARK

State:TX

ZIP:77536

Country:US

Phone:713-479-3491

CAGE:5N484

Company Name:PRO TECHNICAL PRODUCS INC

Address:1220 ROCK ST

Box:City:ROCKFORD

State:IL

ZIP:61101

Country:US

Phone:815-964-7940

CAGE:4V314

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE

SPECIFIED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/CC; A1;9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:TOXIC BY INHALATION OF DUST.
ACUTE:DUST MAY CAUSE IRRITATION TO THE EYES, SKIN AND REPIRATORY
TRACK. CHRONIC:INHALATION OF ASBESTOS FIBERS MAY CAUSE ASBESTOSIS
AND MESOTHELIOMA. SMOKING GREATLY ENHANC ES TH
E RISK OF ASBESTOSIS.
Effects of Overexposure:IRRITATION, COUGHING, DIFFICULTY IN BREATHING,
SHORTNESS OF BREATH, CHEST &/OR ABDOMINAL PAIN.
Medical Cond Aggravated by Exposure:BRONCHIAL HYPER-REACTIVITY,
PUMONARY DISEASES.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. EYE CONTACT:FLUSH WITH WATER
FOR 15 MINUTES. SEE PHYSICIAN IF IRRITATION PERSIST. SKIN
CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPT
OMS
PERSIST. INGESTIO N:DO NOT INDUCE VOMITING, CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Extinguishing Media:WATER
Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPED WITH
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:PICK UP MATERIAL. VACUUM UP POWDER. DO NO
CREATE DUST. USE RESPIRATORY PROTECTION FOR DUSTY COND
ITIONS.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CREATING DUST. DO NOT SAND OR
DRY SWEEP WITHOUT RESPIRATORY PROTECTION.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE UNDER NORMAL CONDITIONS. WEAR NIOSH
APPROVED DUST RESPIRATOR WHEN SANDING, ABRASING OR DRY SWEEPING
ASBESTOS DUST.
Ventilation:LOCAL
Protective Gloves:NON

E

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYEWASH

Work Hygienic Practices:DO NOT SMOKE WHILE SANDING, BRADING OR SWEEPING DUST.

Supplemental Safety and Health

FINISHED PRODUCT IN SPIRAL WOUND GASKETS.

===== Physical/Chemical Properties =====

HCC:T6

Vapor Density:0

Spec Gravity:2.5

Solubility in Water:INSOLUBLE

Appearance and Odor:SOLID COMPOSITE MATERIAL, LIGHT BLUE, NO ODOR.

Percent Volatiles by Volume:00

===== Stability and React

ivity Data =====

Stability Indicator/Materials to Avoid:YES

HYDROFLOURIC ACID AND CONCENTRATED ALKALI.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:ASBESTOS FIBERS.

===== Disposal Considerations =====

Waste Disposal Methods:STANDARD LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.