

MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED -- UNKNOWN -- 2530-00-057-2895  
===== Product Identification =====

MSDS Date:12/09/1992

FSC:2530

NIIN:00-057-2895

MSDS Number: BPMPB

=== Responsible Party ===

Company Name:MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED

Box:3990

City:COLUMBUS

State:OH

ZIP:43216-5000

Country:US

Info Phone Num:614-238-3131

Preparer's Name:HMIS TECHNICIAN

CAGE:JO772

==

= Contractor Identification ===

Company Name:DEFENSE CONSTRUCTION SUPPLY CENTER

Address:NONE

Box:3990

City:COLUMBUS

State:OH

ZIP:43215-5000

Country:US

Phone:614-238-3131

CAGE:16236

Company Name:MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED

Address:700 ROBBINS AVENUE

Box:3990

City:PHILADELPHIA

State:PA

ZIP:19111-5096

Country:US

Phone:215-697-2000

CAGE:JO772

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9293

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.

INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF  
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &  
MESOTHELIOMA, ALL OF WHICH ARE DIS

ABLING AND FATAL D ISEASES OF THE

LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER  
OF THE BOWEL.

Explanation of Carcinogenicity:ASBESTOS IS A KNOWN HUMAN CARCINOGEN.

Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH

THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:  
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.

DIARRHEA, VOMITING, AND NA USEA.

Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERC  
ULOSIS

ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE

THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH

THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.

INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

=====  
===== Fire Fighting Measures =====

Flash Point:

NOT REQUIRED

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED  
VACUUM. THE EQUIPMENT SHALL B

E USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP CONTAMINATION.

==== Handling and Storage =====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE

INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HE

PA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. MANUFACTURER IS UNKNOWN OR OUT OF BUSINESS.

==== Physical/Chemical Properties ==

HCC:T6

Solubility in Water:INSOLUBLE

Appearance and Odor:DRY, FRICTION LINING (BRAKE SHOE)

Percent Volatiles by Volume:0

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST

Hazardous Decomposition Products:ASBESTOS DUST

==== Disposal Considerations =====

Waste Disposal

Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.

PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or impl

ied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.