View NSN Online: https://aerobasegroup.de/nsn/1660-00-285-7774

Product ID:A FLOTATION FIBER, CM-26, CR-26 MSDS Date:10/01/1991 FSC:1660 NIIN:00-285-7774 MSDS Number: BPPLD === Responsible Party === Company Name: MANVILLE SALES CORP Address:717 17TH ST City:DENVER State:CO ZIP:80127 Country:US Info Phone Num:303-978-4900/-2000 Emergency Phone Num:303-978-49 00 CAGE:75165 === Contractor Identification === Company Name:SCHULLER INTERNATIONAL INC. Box:5108 **City:DENVER** State:CO ZIP:80217-5108 Country:US Phone:303-978-4900 CAGE:75165 Company Name: THERMAL STRUCTURES INC Address:2362 RAILROAD ST Box:City:CORONA State:CA ZIP:91720 Country:US Phone:714-736-9911 CAGE:54787

Ingred Name:FIBROUS GLASS CAS:65997-17-3 Fraction by Wt: 80 - 99% Other REC Limits:1 F/CC (MFR) OSHA PEL:5 MG/M3 RDUS T (MFR) ACGIH TLV:10 MG/M3 TDUST (MFR)

Ingred Name:UREA EXTENDED PHENOL-FORMALDEHYDE RESIN CURED CAS:25104-55-6 Fraction by Wt: 1 - 20% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-WOVEN FACINGS, OR VINYL COATINGS Fraction by Wt: < 1% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:UNKNOWN OSHA:NO Health Hazards Acute and Chronic:ACU

TE- THE FIBERS FROM THIS PRODUCT ARE MECHANICAL IRRITANTS & MAY CAUSE TRANSITORY IRRITATION TO EXPOSED AREAS SUCH AS EYES, SKIN & UPPER RESPIRATORY TRACTS. CHRONIC-ANIMAL INHALATION STUDIES HAVE NO T SHOWN ANY IRREVERSIBLE DISEASE EFFECTS RELATED TO FIBER GLASS EXPOSURE. MAY INCREASE THE RATE OF LUNG CANCER.

Explanation of Carcinogenicity:IARC CLASSIFIED GLASS WOOL AS "POSSIBLY CARCINOGENIC TO HUMANS" (CLASS 2B), PER MSDS.

Effects of Overexposure: THE FIBERS FROM THIS PROD

UCT ARE MECHANICAL

IRRITANTS & MAY CAUSE TRANSITORY IRRITATION TO EXPOSED AREAS SUCH AS EYES, SKIN & UPPER RESPIRATORY TRACTS. LONG TERM ANIMAL INHALATION STUDIES HAVE NOT SHO WN ANY IRREVERSIBLE DISEASE EFFECTS RELATED TO FIBER GLASS EXPOSURE. MAY INCREASE THE RATE OF LUNG CANCER.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS OR EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

=====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYE/SKIN: FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL: FLUSH OUT MOUTH WITH WATER. SEEK MEDICAL ATTENTION.

Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS

COOL & FLUSH SPILLS AWAY.
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:MAY PRODUCE CARBON MONOXIDE, CARBON
DIOXIDE, CARBON PARTICLES AND TRACE OF HYDROGEN CYANIDE.
======================================
Spill Release Procedures: PICK UP LARGE PIECES. WEAR APPROVED RESPIRATOR AND CHEMICALLY COMP ATIBLE GLOVES IF NEEDED. VACUUM OR SWEEP UP SPILLAGE. AVOID CREATING DUST. PLACE SPILLAGE IN APPROPRIATE CONTAINER FOR WASTE DISPOSAL. VENTILATE AREA AND WASH SPILL SITE. Neutralizing Agent: NOT APPLICABLE.
======================================
Handling and Storage Precautions:STORAGE-STORE IN COOL, DRY PLACE. Other Precautions:KEEP CONTAINER CLOSED. AVOID INHALATION OF POWDER. AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY AFTER HANDLING MATERI
AL.
======================================
Respiratory Protection:NONE NORMALLY REQUIRED. IF WORKPLACE EXPOSURE LIMIT IS EXCEEDED, A NIOSH APPROVED AIR SUPPLIED RESPIRATOR OR DUST RESPIRATOR IS ADVISED. Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).
Protective Gloves:LEATHER OR COTTON Eye Protection:GOGGLES
Other Protective Equipment: EYE WASH STATION, EMERGENCY SHOWER
Work Hygienic Practices:DO NOT PERMIT EATING, DRINKING OR SMOKING NEAR THIS MATERIAL. Supplemental Safety and Health
======================================
HCC:N1 Melt/Freeze Pt:M.P/F.P Text:>1300F,>704 Spec Gravity:VARIABLE Solubility in Water:NIL Appearance and Odor:GOLD TO YELLOW FIBROUS GLASS BLANKET - NO SIGNIFICANT ODOR
======================================
Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition t

o Avoid:FIRE

Hazardous Decomposition Products:MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE, CARBON PARTICLES AND TRACE OF HYDROGEN CYANIDE.

Waste Disposal Methods: WASTES ARE NOT HAZARDOUS AS DEFINED BY RCRA (40 CFR 261). COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defen

se. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.