

J & R INDUSTRIES INC. -- WS-516 BASE COMPOUND -- 8030-00-286-9035

=====
Product Identification
=====

Product ID:WS-516 BASE COMPOUND

MSDS Date:01/31/1992

FSC:8030

NIIN:00-286-9035

Kit Part:Y

MSDS Number: BPRFX

=== Responsible Party ===

Company Name:J & R INDUSTRIES INC.

Address:800 EAST ANAHEIM STREET

City:WILMINGTON

State:CA

ZIP:90744

Country:US

Info Phone Num:301-476-7121/213-830-9904

Emergency

Phone Num:310-476-7121

Preparer's Name:DR R J MOUALIM

CAGE:DO380

=== Contractor Identification ===

Company Name:J & R INDUSTRIES, INC

Address:800 EAST ANAHEIM STREET

City:WILMINGTON

State:CA

ZIP:90744

Phone:310-476-7121

CAGE:DO380

Company Name:J AND R INDUSTRIES (FACTORY LOCATION)

Address:800 E. ANAHEIM ST

Box:City:WILMINGTON

State:CA

ZIP:90744

Country:US

Phone:310-476-7121

CAGE:7X230

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108

-88-3
RTECS #:XS5250000
Fraction by Wt: 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:INACTIVE INGREDIENTS
Fraction by Wt: 96%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:ANEMIA, STOMACH CRAMPS, MUSCLE & JOINT PAIN, NEUROMUSCULAR DYSFUNCTION, KIDNEY DAMAGE.
Effects of Overexposure:NAUSEA, IRRITATION, WEAKNESS, HEADACHES, METALLIC TASTE.
Medical Cond Aggravated by Exposure:ANEMIA, STOMACH CRAMPS, MUSCLE & JOINT PAIN, NEUROMUSCULAR DYSFUNCTION, KIDNEY DAMAGE.

=====
===== First Aid Measures =====

First Aid:USE NIOSH APPROVED RESPIRATORS, GLOVES & GOGGLES. INGESTION: INDUCE VOMITING. WASH EYES & SKIN WITH PLENTY OF SOAP AND WATER. IN ALL CASES, CONTACT PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Poin
t:NONE
Extinguishing Media:STANDARD COMMERCIAL EXTINGUISHER
Fire Fighting Procedures:USE A POSITIVE PRESSURE SELF CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:COMBUSTIBLE. KEEP ALL SOURCES OF HEAT & SPARKS AWAY. WEAR PROTECTIVE EQUIPMENT. CLEAN UP SPILL IMMEDIATELY.

=====
===== Handling and Storage =====

Handling and Stora

Precautions: COMBUSTIBLE. STORE IN A COOL, DRY PLACE AWAY FROM SPARKS, HEAT & OPEN FLAME. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR NIOSH APPROVED RESPIRATOR.

Ventilation: MECHANICAL VENTILATION

Protective Gloves: GLOVES

Eye Protection: GOGGLES

Other Protective Equipment: CLEAN WATER SHOULD BE AVAILABLE IN THE WORK AREA FOR FLUSHING SKIN & EYES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: 232F, 111C

Decomp Temp: Decomp Text: 302F, 150C

Vapor Density: 3.2

Spec Gravity: 1.50 (WATER=1)

Evaporation Rate & Reference: 0.8

Solubility in Water: