

PERMATEX INDUSTRIAL DIV OF LOCTITE CORPORATION -- 5 GL SEALANT 1372 HITEMP --
8030-00-599-7753

===== Product Identification =====

Product ID:5 GL SEALANT 1372 HITEMP

MSDS Date:01/02/1991

FSC:8030

NIIN:00-599-7753

MSDS Number: BPRHW

=== Responsible Party ===

Company Name:PERMATEX INDUSTRIAL DIV OF LOCTITE CORPORATION

Address:705 N MOUNTAIN RD

Box:11915

City:NEWINGTON

State:CT

ZIP:06111-1411

Countr

y:US

Info Phone Num:800-641-7376 / 203-677-7727

Emergency Phone Num:800-641-7376 /203-677-7727

Preparer's Name:STEPHEN REPETTO

CAGE:62377

=== Contractor Identification ===

Company Name:PERMATEX INDUSTRIAL

Address:HARTFORD SQUARE N 10 COLUMBUS BLVD

Box:City:HARTFORD

State:CT

ZIP:06106

Country:US

Phone:877-376-2839

CAGE:62377

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identificatio

n =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYE IRRITANT. MODERATELY TOXIC BY
INGESTION.

Effects of Overexposure:VAPOR ABOVE TLV IS IRRITATING TO EYES, NOSE,
THROAT AND CAN CAUSE HEADACHE, DIZZINESS, NAUSEA.

===== First Aid Measures =====

First Aid:INGEST: INDUCE VOMITING. OBTAIN MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN
MEDICAL ATT

ENTION. SKIN: FLUSH WITH WATER. EYE: FLUSH AT LEAST 15
MINUTES WITH WATER. OB TAIN MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:60.0F,15.6C
Lower Limits:2.3
Upper Limits:12.7
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES. SOAK UP IN AN INERT
ABSORBE
NT. MAINTAIN ADEQUATE VENTILATION. STORE IN A CLOSED
CONTAINER UNTIL DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT OR FLAME. AVOID
PROLONGED SKIN CONTACT. KEEP AWAY FROM EYES. AVOID PROLONGED
BREATHING OF VAPORS.

=====
Exposure Controls/Personal Protection
=====

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling
Pt:B.P. Text:180F,82C
Vapor Pres:33 @ 68F
Vapor Density:2.07
Spec Gravity:1.1 @ 77 F
Evaporation Rate & Reference:7.7 (ETHER=1)
Solubility in Water:PARTIAL
Appearance and Odor:BLACK PASTE/ALCOHOLIC ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products:NONE

=====
Disposal Considerations
=====

Waste Disposal Methods:INCINERATE FOLLOWING EPA AND LOC

AL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.