View NSN Online: https://aerobasegroup.de/nsn/8010-00-656-1639

## BAKER SEALANTS AND COATINGS CO -- RAW LINDSEED OIL -- 8010-00-656-1639

Product ID:RAW LINDSEED OIL

MSDS Date:10/05/1989

FSC:8010

NIIN:00-656-1639

MSDS Number: BPRJF === Responsible Party ===

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Info Phone Num:201-333-6986 / FAX 201-333-6955

Fm

ergency Phone Num:201-333-6986 Preparer's Name:MARIO NAVARRO

CAGE:34094

=== Contractor Identification ===

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306 Country:US

Phone:201-333-6986

CAGE:34094

Company Name: STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

======= Composition/Information on Ingredients ========

Ingred Name:LINSEED OIL (RAW LINSEE

CAS:8001-26-1 RTECS #:OI9690000 Other REC Limits:NONE SPECIFIED
=========== Hazards Identification ============
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Health Hazards Acute and Chronic:NONE
======================================
First Aid:EYES: FLUSH WITH CLEAN WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER AND OBSERVE ROUTINE HYGIENIC PRACTICES.
======================================
Flash Point Method:CC Flash Point:>200F,>93C Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM, CARBON DIOXIDE, Fire Fighting Procedures:WATER/FOAM MAY CAUSE FROTHING IF DIRECTED INTO CNTNR OF BURNING LIQUID. FIRE FIGHTER SHOULD WEAR PROTECTIVE CLOTHES. USE WATER TO KEEP FIRE EXPOSED CNTNRS COOL.  ==================================
Spill Release Procedures:LARGE SPILLS: MAY BE SCOOPED UP AND PUT INTO CONTAINERS OR SALVAGED. SMALL SPILLS: SPILL MAY BE PICKED UP WITH ABSORBENT MATERIAL AND TRANSFERRED TO CONTAINERS.  ===================================
Handling and Storage Precautions:STORE AWAY FROM HIGH TEMPERATURES AND FLAMES. DO NOT BREATHE SPRAY MIST.  Other Precautions:AVOID SPONTANEOUS COMBUSTION OF CONTAMINATED RAGS & EASILY IGNITABLE ACCUMULATIONS (SUCH AS SPRAY BOOTH RESIDUES) BY IMMEDIATE IMMERSION IN

D OIL IS NOT A HAZARDOUS MATERIAL

UNDER CURRENT DEPARTMENT OF LABOR DEFINITIONS)

WATER. EMPTIED CONTAINERS MAY RETAIN RESIDUES OF PRODUCT. DO NT CUT, PUNCTURE, WELD ON/NEAR CNTNRS.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NOT NORMALLY NEEDED Protective Gloves: NEOPRENE RUBBER GLOVES

Eye Protection: GOGGLES OR SIDE SHIELD SPECTACLES

Supplemental Safety and Health

======== Physical/Chemical Properties ============

HCC:N1 Spec Gravity:0.92 Appearance and Odor:AMBER LIQUID Percent Volatiles by Volume:0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDES ARE
POSSIBLE

======= Disposal Considerations ===========

Waste Disposal Methods:SEE OTHER PRECAUTIONS BELOW. CAREFULLY INCINERATE OR USE SECURE LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with thi

s information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.