

TACC INTERNATIONAL CORP. -- NEOPENE SOLVENTBORNE ADHESIVE MA 102 -- 8040-00-142-9913

=====
Product Identification
=====

Product ID:NEOPENE SOLVENTBORNE ADHESIVE MA 102

MSDS Date:01/01/1987

FSC:8040

NIIN:00-142-9913

Kit Part:Y

MSDS Number: BPTVX

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

In

fo Phone Num:617-878-7015

Emergency Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 40-45%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt

Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 30-36%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VOC: 663 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE SIGNS OF OVEREXPOSURE COULD BE
HEADACHE, D
IZZINESS, NAUSEA, UPPER RESPIRATORY DRYNESS OR
IRRITATION, DROWSINESS, MENTAL DEPRESSION OR NARCOSIS, DIFFICULTY
BREATHING. CHRONIC EFFECTS OF OVEREXPOSURE TO SOLVENT VAPORS COULD
LEAD TO PERMANENT EFFECTS TO NERVOUS SYSTEM, BODY ORGANS OR BRAIN.
SKIN: REMOVAL OF SKIN
Effects of Overexposure:OILS, IRRITATION, DERMATITIS, EVEN
SENSITIZATION WITH LONG OVEREXPOSURE. EYES: IRRITATION. INGESTION:
MAY BE HARMFUL OR FATAL IF SWALLOWED.

=====
===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR, IF NECESSARY, CALL A PHYSICIAN.
SKIN: WASH WITH MILD SOAP AND WATER, APPLY A MILD CREAM. EYES:
FLUSH WITH WATER AT LEAST 15 MINUTES. INGESTION: CALL POISON CENTER
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:1
Solubility in Water:NIL
Appearance and Odor:NEUTRAL, AROMATIC ODOR
Percent Volatiles by Volume:78

=====
===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES

Stability Condition to Avoid: FIRE, SPARKS, STATIC ELECTRICITY

Hazardous Decomposition Products: CARBON MONOXIDE, AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.