

FARWEST PAINT MFG CO -- EXT. ACRYLIC LATEX FOR WOOD & MASONRY WHITE --
8010-00-419-8541

===== Product Identification =====

Product ID:EXT. ACRYLIC LATEX FOR WOOD & MASONRY WHITE

MSDS Date:10/01/1992

FSC:8010

NIIN:00-419-8541

MSDS Number: BPTZC

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:2

06-244-8844

Emergency Phone Num:206-941-1619

Preparer's Name:NORMA HABEEB

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA 313)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1.59%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

EPA

Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:GLYCOL ETHER (SARA 313)
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 1.04%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:VOC: 94 GRAMS/LITER (LESS WATER)
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:
INHALE: PROLONGED INHALATION IN
 CONFINED AREAS, MAY LEAD TO MUCOUS MEMBRANE
 IRRITATION/DIZZINESS/HEADACHE. SKIN: IRRITATION. EYE: IRRITATION.
INGEST: AMOUNTS INGESTED INCIDENTAL TO CONSUMER/INDUSTRIAL
HANDLING ARE NOT LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF
LARGER AMOUNTS COULD CAUSE SERIOUS INJURY.
Effects of Overexposure:NONE
Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:INHALE: PROLONGED INH
ALATION IN CONFINED AREAS, MAY LEAD TO
MUCOUS MEMBRANE IRRITATION/DIZZINESS/HEADACHE. SKIN: IRRITATION.
EYE: IRRITATION. INGEST: AMOUNTS INGESTED INCIDENTAL TO CONSUMER
AND INDUSTRIAL HANDLING ARE NOT LIKELY TO CAUSE INJURY, HOWEVER,
INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Extinguishing Media:DRY CHEMICAL, WATER, WATER FOG
Fire Fighting Procedures:WATER MAY BE USED TO CO

OL AND PROTECT ADJACENT
CONTAINERS.

Unusual Fire/Explosion Hazard:WILL NOT BURN. CLOSED CONTAINERS MAY
RUPTURE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED
WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID
TEMPERATURES BELOW 40F. KEEP
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND
APPROPRIATELY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW
APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC
VAPOR/ PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF
EXPOSURE IS MAINTAINED BELOW APPLICABLE
EXPOSURE LIMITS.

Protective Gloves:PROTECTIVE GLOVES

Eye Protection:SAFETY GOGGLES W/UNPERFORATED SIDESHIELD

Other Protective Equipment:EYE WASH/SAFETY SHOWERS/GOGGLES/SAFETY
GLASSES/IMPERVIOUS GLOVES.

Work Hygienic Practices:KEEP WORK AREA CLEAN/FREE OF SPILLS/LEAKS.
ALWAYS WASH HANDS THOROUGHLY W/SOAP/WATER BEFORE HANDLING
FOOD/DRINK/SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:23.8 @ 20C

Vapor Density:>AIR

Spec Gravity:1.3896

pH:7.0

Viscosity:75-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR, COLOR OF TINT.

Percent Volatiles by Volume:3.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS AND/OR HYDROFLUORIC ACID.

Stability Condition to Avoid:ELEVATED TEM

PERATURES, CONTACT WITH
OXIDIZING AGENTS.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no
manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.