

TACC INTERNATIONAL CORP. -- NEOPRENE SOLVENTBORNE ADHESIVE MA 102 --
8040-00-515-2246

=====
===== Product Identification =====

Product ID:NEOPRENE SOLVENTBORNE ADHESIVE MA 102

MSDS Date:01/01/1987

FSC:8040

NIIN:00-515-2246

Kit Part:Y

MSDS Number: BPTZQ

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone Num:617-878-7015

Emergency Phone Num:617-878-7015/800-424-9300

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 40-45%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PP

M; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 30-36%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VOC: 663 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazard

s Acute and Chronic:INHALATION: ACUTE SIGNS OF
OVEREXPOSURE COULD BE HEADACHE, DIZZINESS, NAUSEA, UPPER
RESPIRATORY DRYNESS OR IRRITATION, DROWSINESS, MENTAL DEPRESSION OR
NARCOSIS, DIFFICULTY IN BREATHING. CHRONIC EFFEC TS OF OVEREXPOSURE
TO SOLVENT VAPORS COULD LEAD TO PERMONENT NERVOUS SYSTEM/BODY
ORGANS/BRAIN EFFECTS. USE **

Effects of Overexposure:**WITH ADEQUATE VENTILATION. EYES: IRRITATION.
INGESTION: MAY BE HARMFUL OR FATAL IF SWALLOWED. SKIN: REMOVAL OF
SKIN
OILS, IRRITATION, DERMATITIS, EVEN SENSITIZATION WITH
OVEREXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR. EYES: IF NECESSARY CALL A
PHYSICIAN. FLUSH WITH WATER FOR AT LEAST 15 MINUTES, IF NECESSARY,
CALL A PHYSICIAN. SKIN: WASH WITH MILD SOAP AND WATER APPLY A MILD
CREAM. INGEST ION: CALL POISON CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:>20F,>-7C
Low

er Limits:1.1

Upper Limits:7.5

Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG

Fire Fighting Procedures:AVOID BREATHING SMOKE. USE AIR SUPPLD RESCUE
EQUIP FOR ENCLOSED AREAS. WATER TENDS TO SPREAD BURNING LIQUID IF
LARGE AMOUNTS USED.

Unusual Fire/Explosion Hazard:EXTREME FLAMM. VAPOR MAY IGNITE

EXPLOS/FLASH FIRE. ELIMINATE IGNIT SOURCE. NO SMOKING. CROSS VENT
TO REMOVE VAPOR/ SOLVENT ODOR. ELEC GROUND CNTNRS WHEN TRANSFE

===== Accidental Release Me

asures =====

Spill Release Procedures:SMALL QUANTITIES MAY BE ABSORBED INTO AN
APPROPRIATE ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
STORE AT 60-95F OUT OF SUN. USE ADEQUATE VENTILATION TO AVOID
BREATHING VAPOR WHEN COVER REMOVED.

Other Precautions:GROUND ALL EQUIPMENT WHEN HANDLING FLAMMABLE
SOLVENTBORNE MATERIALS.

===== Exposure Controls/Person

al Protection =====

Respiratory Protection:IF VAPORS EXCEED TLV, USE SELF CONTAINED ORGANIC
MASK NIOSH APPROVED.

Ventilation:SUFFICIENT TO KEEP WORKROOM CONCENTRATION BELOW TLV.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES OR FACE SHIELD.

Other Protective Equipment:BARRIER CREAM FOR SENSITIVE SKIN.

Supplemental Safety and Health

KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:156F,69C

Vapor Pr

es:73 @ 20C

Vapor Density:>1

Spec Gravity:0.72

Evaporation Rate & Reference:>1

Solubility in Water:NIL

Appearance and Odor:NEUTRAL, AROMATIC ODOR

Percent Volatiles by Volume:78

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY

Hazardous Decomposition Products:CO AND CO2.

===== Disposal Considerations

=====

Waste Disposal Methods:MATERIAL IS DESIGNATED AS HAZARDOUS WASTE UNTIL ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implie

d, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.