

TACC INTERNATIONAL CORP. -- CONTACT CEMENT -- 8040-00-779-9595

=====
Product Identification
=====

Product ID:CONTACT CEMENT

MSDS Date:01/01/1987

FSC:8040

NIIN:00-779-9595

MSDS Number: BPVCS

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone Num:617-878-7015

Emergency Phone Num:617-878-7

015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 42-50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTEC

S #:XS5250000
Fraction by Wt: 15-18%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 20-25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 645 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HEADACHE, DIZZINESS, NAUSEA, UPPER
RESPIRATOR DRYNESS, IRRITATION, DROWSINESS, MENTAL DEPRESSION,
NARCOSIS, DIFFICULTY BREATHING. PERMANENT EFFECTS TO NERVOUS
SYSTEM, BODY ORGANS OR BRAIN. USE W/ADEQU ATE VENTILATION. SKIN:
REMOVAL OF SKIN OILS, IRRITATION, DERMATITIS, EVEN SENSITIZATION
W/LONG OVEREXPOSURE. *
Effects of Overexposure:* EYE: IRRITATION. INGESTION: MAY B
E HARMFUL OR
FATAL IF SWALLOWED.

=====
===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR, IF NECESSARY, CALL A PHYSICIAN.
SKIN: WASH WITH MILD SOAP AND WATER, APPLY A MILD CREAM. EYES:
FLUSH WITH WATER AT LEAST 15 MINUTES. INGESTION: CALL POISON CENTER
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:1 (BU AC=1)
Solubility in Water:NIL
Appearance and Odor:KETON

E ODOR/CLEAR

Percent Volatiles by Volume:80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS. STRONG ACIDS AND STRONG BASES.

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY.

Hazardous Decomposition Products:CARBON MONOXIDE, AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL RE

GULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY
WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility
for the suitability of this information to their
particular situation.