

CHEMICOAT, INC -- COATING COMPOUND, PAINT ANTISWEAT -- 8010-00-965-2507

=====  
Product Identification  
=====

Product ID:COATING COMPOUND, PAINT ANTISWEAT

MSDS Date:10/24/1990

FSC:8010

NIIN:00-965-2507

MSDS Number: BPVFL

=== Responsible Party ===

Company Name:CHEMICOAT, INC

Address:5063 HAPPY HOLLOW RD

City:ATLANTA

State:GA

ZIP:30360

Country:US

Info Phone Num:404-457-2657

Emergency Phone Num:404-457

-2657

CAGE:MO394

=== Contractor Identification ===

Company Name:CHEMICOAT, INC

Address:5063 HAPPY HOLLOW RD

City:ATLANTA

State:GA

ZIP:30360

Country:US

Phone:404-457-2657

CAGE:MO394

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARDOUS MATERIAL

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:AVOID INHALATION OF SPRAY DUST. DO NOT TAKE BY INGESTION. PEOPLE WITH ACUTE DERMATITIS MAY BE AFFECTED. WASH OFF THE MATERIAL AS QUICKLY AS POSSIBLE. PEOPLE WITH RESPIRATORY DISORDERS, SHOULD NOT BE S UBJECTED TO SPRAY DUST OR SPRAY MIST.

Effects of Overexposure:IN CASES OF DERMATITIS THERE COULD BE A REDDENING OF THE SKIN. IN CASES OF RESPIRATORY DISORDERS, COUGHING OR SNEEZING MAY OCCUR.

Medical Cond Aggravated by Exposure:NONE HAVE BEEN OBSERVED OR REPORTED.

===== First Aid Measures =====

First Aid:IN CASE OF PROLONGED SKIN CONTACT, WASH WITH SOAP AND WATER. IN CASE OF CONTACT WITH EYES, WASH WITH COPIOUS AMOUNT OF WATER.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:NF

Extinguishing Media:NONE REQUIRED

Fire Fighting Procedures:NONE REQUIRED

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTR EME HEAT OR FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:IF THIS MATERIAL IS SPILLED OR RELEASED, SOAK UP WITH ABSORBENT MATERIAL AND DISPOSE OF IN APPROVED LANDFILL.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F OR BELOW 40F. EXCESS TEMPERATURES WILL CAUSE THE EMULSION TO COAGULATE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE FACE MASK WHEN APPLYING BY PRESSURE OR AIRLESS SPRAY.

Ventilation:USE LOCAL EXHAUST. MECHANICAL (GENERAL) RECOMMENDED.

Protective Gloves:NOT REQUIRED

Eye Protection:USE GOGGLES WHEN SPRAYING

Other Protective Equipment:COVERALLS

Work Hygienic Practices:KEEP WORKPLACE CLEAN.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:AS WATER

Vapor Density:1

Spec Gravity:1.20 (WATER=

1)  
Evaporation Rate & Reference:>1 (BU AC=1)  
Solubility in Water:COMPLETE DISPERSIBLE  
Appearance and Odor:VISCOUS PASTE, NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID STRONG OXIDIZERS  
Stability Condition to Avoid:AVOID STRONG OXIDIZERS  
Hazardous Decomposition Products:NONE KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:APPROVED LANDFILL.

Disclaimer (provided  
with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.