

UNION CARBIDE CHEMICALS & PLASTICS CO., INC. -- 11507453 NEODYMIUM DOPED YTRIUM ALUMINUM GA -- 1260-01-073-5886

===== Product Identification =====

Product ID:11507453 NEODYMIUM DOPED YTRIUM ALUMINUM GA
MSDS Date:05/01/1991
FSC:1260
NIIN:01-073-5886
MSDS Number: BPWYY
=== Responsible Party ===
Company Name:UNION CARBIDE CHEMICALS & PLASTICS CO., INC.
Address:750 S 32ND STREET
City:WASHOUGAL
State:W
A
ZIP:98671
Country:US
Info Phone Num:206-835-8566
Emergency Phone Num:800-822-4357
CAGE:DO713
=== Contractor Identification ===
Company Name:UNION CARBIDE CHEM & PLASTICS CO INC
Address:39 OLD RIDGEBURY RD
City:DANBURY
State:CT
ZIP:06817-0001
Phone:203-794-6753/304-744-3487
CAGE:DO713

===== Composition/Information on Ingredients =====

Ingred Name:NEODYMIUM OXIDE
CAS:1313-97-9
Fraction by Wt: 0.85%
Other REC Limits:NONE RECOMMENDED

Ingred Name:YTRIUM OXIDE
CAS:1314-36-9
RTEC

S #:ZG3850000
Fraction by Wt: 56.88%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS
FORMS) (SARA III)
CAS:1344-28-1
RTECS #:BD1200000
Fraction by Wt: 42.83%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards A
cute and Chronic:NO EVIDENCE OF ADVERSE EFFECTS.
Effects of Overexposure:NO EVIDENCE OF ADVERSE EFFECTS.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER.
INHALATION: REMOVE TO FRESH AIR. INGESTION: NO HARMFUL EFFECTS.

===== Fire Fighting Measures =====

Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPRIATE
FOR
SURROUNDING FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:BROKEN CRYSTALS HAVE SHARP EDGES. GLOVES
SHOULD BE WORN WHEN CLEANING UP A BROKEN CRYSTAL.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL PRECAUTIONS COMMON TO SAFE
MANUFACTURING PRACTICES SHOULD BE FOLLOWED IN HANDLING AND STORAGE.
ALWAYS MACHINE A CRYSTAL USING WET METHODS.
Other Precautions:USE OF THIS CRYST

AL IN LASER OPERATIONS SHOULD BE
SUPERVISED BY QUALIFIED, KNOWLEDGEABLE PERSONNEL, IN ACCORDANCE
WITH ANSI Z 136.1, THE AMERICAN NATIONAL STANDARD FOR THE SAFE USE
OF LASERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXCESSIVE DUSTING OCCURS WHEN MACHINING, WEAR
NIOSH OR MSHA APPROVED DUST RESPIRATOR.

Ventilation:LOCAL DUST PICK UP RECOMMENDED WHEN MACHINING.

Protective Gloves:RECOMMENDED.

Eye Protection:SAFETY GLASSES.

Other

Protective Equipment:NONE

Work Hygienic Practices:STANDARD PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

PROLONGED CONTACT WITH DUST OR POWDER FROM MACHINING MAY CAUSE DRYING
OF SKIN. *** NOTE: THIS IS AN ARTICLE. MANUFACTURER SUPPLIED MSDS
FOR MANUFACTURING OPERATIONS ***

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:3578F,1970C

Spec Gravity:4.55

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TRANSPAR

ENT, PURPLE. NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ETHYLENE OXIDE, CHROMIUM TRIFLUORIDE.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

T

his information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.