

TECHNACELL DIVISION OF POWER-SONIC -- EP6330-34 BATTERY -- 6140-01-090-6667

=====  
Product Identification  
=====

Product ID:EP6330-34 BATTERY

MSDS Date:06/05/1986

FSC:6140

NIIN:01-090-6667

MSDS Number: BPWYZ

=== Responsible Party ===

Company Name:TECHNACELL DIVISION OF POWER-SONIC

Address:1444 30TH STREET

City:SAN DIEGO

State:CA

ZIP:92154

Country:US

Info Phone Num:619-575-2275

Emergency Phone Num:61

9-575-2275

CAGE:MO895

=== Contractor Identification ===

Company Name:TECHNACELL DIVISION OF POWER-SONIC

Address:1444 30TH STREET

Box:City:SAN DIEGO

State:CA

ZIP:92154

Country:US

Phone:619-575-2275

CAGE:MO895

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 39.1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name

:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:LITHARGE (LEAD MONOXIDE OR LEAD OXIDE YELLOW)  
CAS:1317-36-8  
RTECS #:OG1750000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.15 MG/M3; 8990

Ingred Name:LEAD PEROXIDE (LEAD DIOXIDE)  
CAS:1309-60-0  
RTECS #:OG0700000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0  
.15 MG/M3(PB); 9192

Ingred Name:LEAD TETROXIDE  
CAS:1314-41-6  
RTECS #:OG5425000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.15 MG/M3 (PB)

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:LD50 ORAL RAT IS 2140 MG/KG.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: SEVERE BURNS AND ULCERATION OF  
SKIN, EYES, MOUTH, THROAT, E  
SOPHAGUS AND STOMACH. INFLAMMATION OF  
BRONCHIAL MEMBRANES. LEAD MAY CAUSE GASTROINTESTINAL DISORDERS AND  
CNS EFFECTS. CHRONIC: EROSION OF TEETH, INFLAMMATION OF NOSE,  
THROATAND BRONCHIAL TUBES. LEAD MAY CAUSE ANEMIA, DAMAGE TO KIDNEYS  
AND CNS.

Explanation of Carcinogenicity:LEAD IS LISTED UNDER IARC AND NTP.  
Effects of Overexposure:IF CONTACTED, SEVERE BURNS AND ULCERATION OF  
SKIN AND EYES. IF INHALED, SEVERE RESPIRATORY IRRITATION. IF  
INGESTED, SEVERE BURNS AND ULCERATI

ON.

Medical Cond Aggravated by Exposure:SULFURIC ACID MAY AGGRAVATE SKIN DISEASES SUCH AS ECZEMA AND DERMATITIS. LEAD CAN AGGRAVATE CHRONIC FORMS OF KIDNEY, LIVER AND NEUROLOGIC DISEASES.

=====  
===== First Aid Measures =====

First Aid:EYES/SKIN: FLUSH WITH PLENTY OF WATER. SEE DOCTOR IMMEDIATELY. REMOVE CONTAMINATED CLOTHING AND SHOES. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: DO NOT INDUCE VOMITING. GIVE MILK OR WATER, FOLLOWED BY 2 OUNCES OF MILK OF MAGNESIA (NO CARBONATES). SEE DOCTOR IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE  
Lower Limits:4.0(HYDROGN)  
Upper Limits:75(HYDROGEN)  
Extinguishing Media:USE CARBON DIOXIDE OR DRY CHEMICAL.  
Fire Fighting Procedures:EVACUATE AREA. REMOVE ALL IGNITION SOURCES. WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.  
Unusual  
Fire/Explosion Hazard:HYDROGEN GAS MAY BE PRODUCED AND MAY EXPLODE IF IGNITED. REMOVE ALL IGNITION SOURCES. VENTILATE AREA.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DILUTE CAUTIOUSLY WITH WATER. COVER WITH SODA ASH OR QUICKLIME. SCOOP UP AND PLACE IN APPROPRIATE DISPOSAL CONTAINER. FLUSH AREA WITH LARGE AMOUNTS OF WATER.  
Neutralizing Agent:SODA ASH (SODIUM CARBONATE), BAKING SODA OR QUICKLIME (CALCIUM OXIDE).

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE AWAY FROM FLAMES, IGNITION SOURCES, COMBUSTIBLE AND ORGANIC MATERIALS. AVOID PROLONGED OVERCHARGING. WEAR PROTECTIVE EQUIPM.  
Other Precautions:DO NOT CARRY BATTERY BY TERMINALS. DO NOT DROP BATTERY, PUNCTURE OR ATTEMPT TO OPEN BATTERY CASE. KEEP TERMINALS COVERED IN PLASTIC CASE. AVOID SHORTING BATTERIES. PLACE BROKEN BATTER

# IES IN PLASTIC CONTAINERS AND DELIVER TO BATTERY RECYCLER

## ===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED CARTRIDGE RESPIRATOR FOR ACIDS OR FULL FACE MASK AS APPROPRIATE FOR EXPOSURE OF CONCERN WHEN TLV IS EXCEEDED.

Ventilation:GENERAL (MECHANICAL) VENTILATION. LOCAL EXHAUST IN CONFINED AREAS.

Protective Gloves:RUBBER GLOVES IF CONTACT IS EXPECTED.

Eye Protection:GOGGLES IF CONTACT IS EXPECTED.

O

Other Protective Equipment:RUBBER APRON AND BOOTS IF CONTACT IS EXPECTED. EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

CLEAN TERMINALS WITH MILD BAKING SODA SOLUTION AND WASH WITH WATER. WHEN BRUSHING BATTERY POSTS, USE MASK APPROVED FOR LEAD DUST, SAFETY GLASSES AND GLOVES.

## ===== Physical/Chemical Properties =====

HCC:Z4

Boiling Pt:=113.9C, 237.F

Melt/Freeze Pt:=-70.C, -94.F

Va

apor Pres:9.95

Vapor Density:>1

Spec Gravity:1.280

pH:ACIDIC

Evaporation Rate & Reference: