

EXXON COMPANY, U.S.A., GOVERNMENT SALES FUELS -- 150 LP SOLVENT NEUTRAL --
9150-00-823-8024

===== Product Identification =====

Product ID:150 LP SOLVENT NEUTRAL

MSDS Date:12/02/1991

FSC:9150

NIIN:00-823-8024

MSDS Number: BPXXT

=== Responsible Party ===

Company Name:EXXON COMPANY, U.S.A., GOVERNMENT SALES FUELS

Address:800 BELL STREET

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info P

hone Num:713-656-3424

Emergency Phone Num:713-656-6449

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

Company Name:SANLO PRODUCTS CO

Address:100 ,MANHATTAN AVE SUITE 103

City:UNION CITY

State:NJ
ZIP:07087
Country:US
Phone:201-348-1684/800-424-9300(CHEMTREC)
CAGE:0K5U0

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC OR DISTILLATES,
SOLVENT-DEWAXED HEAVY PARAFFINIC.
CAS:64742-54-7
RTECS #:PY8035500
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:400F,204
C
Autoignition Temp:Autoignition Temp Text:>260C
Lower Limits:0.9
Upper Limits:7
Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM OR CARBON
DIOXIDE TO EXTINGUISH THE FIRE. USE WATER SPRAY TO COOL FIRE
EXPOSED CONT.
Fire Fighting Procedures:MINIMIZE BREATHING OF GASES, VAPORS, FUMES, OR
DECOMPOSITION PRODUCTS. USE SUPPLIED AIR BREATHING EQUIPMENT FOR
ENCLOSED OR CONFINED SPACES.
Unusual Fire/Explosion Hazard:FUMES, SMOKE, CARBON MONOXIDE, ALDEHYDES
AND OTHER DECOMPOSITI
ON PRODUCTS AE PRODUCED. WATER SPRAY MAY BE
USED TO FLUSH SPILL AWAY FROM EXPOSURE.

=====
Exposure Controls/Personal Protection
=====

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6
Boiling Pt:B.P. Text:556F,291C
Melt/Freeze Pt:M.P/F.P Text:-0F,-18C
Vapor Pres:5
Spec Gravity:0.67
pH:7
Viscosity:156 SSU
Evaporation Rate & Reference: