

KESTER SOLDER COMPANY DIV OF LITTON SYSTEMS INC -- #44 RESIN-CORE SOLDER --
3439-00-133-1108

===== Product Identification =====

Product ID:#44 RESIN-CORE SOLDER

MSDS Date:12/12/1988

FSC:3439

NIIN:00-133-1108

MSDS Number: BPYCQ

=== Responsible Party ===

Company Name:KESTER SOLDER COMPANY DIV OF LITTON SYSTEMS INC

Address:515 E TOUHY

City:DES PLAINES

State:IL

ZIP:60018-2675

Country:US

Info Phone Num

:708-297-1600

Emergency Phone Num:708-297-1600

CAGE:09185

=== Contractor Identification ===

Company Name:KESTER SOLDER COMPANY

Address:515 E. TOUHY AVENUE

Box:City:DES PLAINES

State:IL

ZIP:60018

Country:US

Phone:800-424-9300

CAGE:09185

Company Name:KESTER SOLDER DIVISION OF LITTON SYSTEMS, INC.

Address:515 E. TOUHY AVENUE

Box:City:DES PLAINES

State:IL

ZIP:60018

Country:US

Phone:847-297-1600

CAGE:75297

===== Composition/Information on Ingredients =====

Ingred Name:ROSIN ACID

C

AS:8050-09-7
Fraction by Wt: 95%
Other REC Limits:NONE RECOMMENDED

Ingred Name:FOLLOWING INGREDINTS ARE FOR THE SOLDER WIRE AROUND THE
RESIN. MANUFACTURER DID NOT LIST. THEY ARE FROM PARTSMASER.
RTECS #:9999999ZZ
Other REC Limits:NONE RECOMMENDED

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Fraction by Wt: 61.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9293

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 37.53%
Other REC Limit
s:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)
CAS:7440-36-0
RTECS #:CC4025000
Fraction by Wt: 0.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG SB/M3; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BISMUTH
CAS:7440-69-9
RTECS #:EB2600000
Fraction by Wt: 0.25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:COPPER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
Fr

action by Wt: 0.08%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA III)
CAS:7440-38-2
RTECS #:CG0525000
Fraction by Wt: 0.03%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3 (AS)
ACGIH TLV:0.01,A1 MG/M3; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 0.02%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM (SARA III)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 0.005%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15MG/M3 DUST/5 FUME
ACGIH TLV:10MG/M3 DUST; 9293

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 0.005%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG ZNO/M3
ACGIH TLV:10 MG ZNO/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of

Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SMOKE FOM SOLDERING OPERATIONS
MAY CAUSE RESPIRATORY TRACT AND EYE IRRITATION. ROSIN IS AN
ALLERGIN; MAY CAUSE RASH, HEADACHE, OR THROAT IRRITATION IN A
SENSITIVE PERSON. CHRONIC: NONE SPECIFIE D BY MANUFACTURER.
HMIS-MAY CAUSE CANCER.

Explanation of Carcinogenicity:LEAD IS LISTED BY NTP AS AN ANTICIPATED
CARCINOGEN AND BY IARC AS A SUSPECTED (2B) CARCINOGEN.

Effects of Overexposure:INHALED
: COUGHING, SNEEZING, SHORTNESS OF
BREATH, SORE THROAT. EYES: TEARING, REDNESS, BLURRED VISION. SKIN:
RASH. INGESTED: NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALED: REMOVE TO FRESH AIR. EYES: FLUSH WITH LOTS OF WATER
FOR 15 MINUTES, HOLD LIDS OPEN. SEE DOCTOR. SKIN: WASH WITH SOAP
AND WATER. INGESTED: NONE SPECIFIED BY MANUFACTURER.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:420F,216C
Extinguishing Media:WATER, CARBON DIOXIDE, ALCOHOL FOAM, DRY CHEMICAL
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP OR SCOOP UP AND PLACE IN A CONTAINER FOR
LATER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID EYE CONTACT WITH HOT FLUX. AVOID
BREATHING SMOKE DURING SOLDERING.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:USE ADEQUATE MECHANICAL VENTILATION.
Protective Gloves:NONE NORMALLY REQUIRED.
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE NORMAL

LY REQUIRED.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:149F,65C

Spec Gravity:1.08 (WATER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SOLID AMBER CORE INSIDE SOLDER WIRE

Percent Volatiles by Volume:4.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to A

void:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:CONTACT WITH INCOMPATIBLES. AVOID
TEMPERATURES ABOVE 149F

Hazardous Decomposition Products:MAY EMIT HYDROGEN CHLORIDE FUMES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

o

f Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.