

SPECTRUM CHEMICAL MANUFACTURING CORP. -- PETROLATUM -- 6505-00-133-8025

=====
Product Identification
=====

Product ID:PETROLATUM

MSDS Date:05/10/1991

FSC:6505

NIIN:00-133-8025

MSDS Number: BPYCS

=== Responsible Party ===

Company Name:SPECTRUM CHEMICAL MANUFACTURING CORP.

Address:14422 SOUTH SAN PEDRO STREET

City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Info Phone Num:213-516-8000

Emergency Phone

Num:213-516-8000

CAGE:63415

=== Contractor Identification ===

Company Name:SPECTRUM LABORATORY PRODUCTS INC

Address:14422 S SAN PEDRO ST

Box:City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Phone:310-516-8000/FAX: 310-516-9843

CAGE:63415

=====
Composition/Information on Ingredients
=====

Ingred Name:GREASE, PETROLEUM

CAS:8009-03-8

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inha

lution: YES Skin: NO Ingestion: NO
Reports of Carcinogenicity: NTP: NO IARC: YES OSHA: NO
Health Hazards Acute and Chronic: ACUTE: INHALATION OF MIST MAY CAUSE
RESPIRATORY IRRITATION, LIPID PNEUMONIA/GRANULOMA OF LUNG. CONTACT
WITH SKIN MAY CAUSE HYSENSITIVITY REACTIONS IN SOME. CONTACT WITH
EYES MAY CAUSE IRRITATION. SWALLOWING LARGE AMOUNTS MAY CAUSE
DIGESTIVE SYSTEM IRRITATION. CHRONIC: SKIN CONTACT MAY CAUSE
FOLLICULITIS.

Explanation of Carcinogenicity: IARC LIST MINERAL OILS AS IARC GROUP
3-INADEQUATE EVIDENCE.

Effects of Overexposure: INHALATION: COUGHING, SHORTNESS OF BREATH.
EYES: REDNESS, TEARING, BLURRED VISION, DISCOMFORT. SKIN: RASH,
REDNESS, DISCOMFORT. INGESTED: NAUSEA, VOMITING, DIARRHEA.

Medical Conditions Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid: INHALED: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF
BREATHING STOPPED. GIVE OXYGEN IF BREATHING DIFFICULT. GET MEDICAL
ATTENTION. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS
OPEN. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH
SOAP AND WATER. INGESTED: TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET
MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS.

=====
Fire Fighting Measures
=====

Flash Point Method: COC
Flash Point: >360F, >182C
Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR
REGULAR FOAM

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS. MOVE
CONTAINER FROM FIRE IF CAN BE DONE AT NO RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH PRESSURE WATER.

Unusual Fire/Explosion Hazard: DIKE FIRE CONTROL WATER FOR LATER
DISPOSAL.

=====
Accidental Release Measures
=====

Spill Release Procedures: SWEEP UP AND PLACE IN CONTAINERS FOR LATER
DISPOSAL. DO NOT FLUSH TO SEWER OR WATERWAYS. KEEP UNNECESSARY
PEOPLE AWAY.

Neutralizing Agent:

NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF CONDITIONS WARRANT; USE NIOSH/MSHA APPROVED RESPIRATOR, OR SUPPLIED AIR RESPIRATOR, OR SCBA, AS SITUATION REQUIRES. USE IN ACCORDANCE WITH 29 C

FR

1910.134.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS IF VAPORS OR MISTS GENERATED.

Protective Gloves:RUBBER IF PROLONGED OR REPEATED CONTACT

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:>100F,>38C

Vapor Pres: