

ROYAL LUBRICANTS COMPANY INC. -- AEROSHELL FLUID 18 -- 9150-00-185-0629

=====
Product Identification
=====

Product ID:AEROSHELL FLUID 18

MSDS Date:10/09/1990

FSC:9150

NIIN:00-185-0629

MSDS Number: BPYDS

=== Responsible Party ===

Company Name:ROYAL LUBRICANTS COMPANY INC.

Address:72 EAGLE ROCK AVE

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Info Phone Num:201-887-7410/3100

Emergency Ph

one Num:201-887-7411, CHEMTREC 800-424-9300

CAGE:07950

=== Contractor Identification ===

Company Name:ROYAL LUBRICANTS COMPANY INC.

Address:215 MERRY LN

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Phone:973-887-7411/7410

CAGE:07950

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT
NAPHTHENIC

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 45-55%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:5 M

G/M3 (OIL MIST)

Ingred Name: DISTILLATES, SOLVENT-REFINED LIGHT NAPHTHENIC

CAS: 64741-97-5

RTECS #: PY8041000

Fraction by Wt: 40-50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 300 PPM

ACGIH TLV: 300 PPM

Ingred Name: HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS: 64742-46-7

RTECS #: JN9379645

Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: BARIUM DINONYLNAPHTHALENE SULFONATE

CAS: 25619-56-1

Fraction by Wt: 1-2%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 0.5 MG/M3 (AS BA)

ACGIH TLV: 0.

5 MG/M3 (AS BA)

Ingred Name: MINOR ADDITIVES

Fraction by Wt: 300F, >149C

Extinguishing Media: CO2, DRY CHEMICAL, FOAM OR WATER FOG

Fire Fighting Procedures: WEAR PROPER PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION MAY PRODUCE TOXIC COMPOUNDS OF BORON. NORMAL COMBUSTION FORMS CO2, WATER VAPOR, & MAY PRODUCE OXIDES OF NITROGEN. RESIDUE MAY IGNITE EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures: STOP SOURCE OF LEAK OR RELEASE. CLEAN UP SPILLS USING APPROPRIATE TECHNIQUES SUCH AS ABSORBING MATERIALS OR PUMPING. REMOVE CONTAMINATED SOIL. CONTAIN LIQUID TO PREVENT FURTHER CONTAMINATION OF SOIL, SURFACE WATER OR GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AWAY FROM FLAMES.

Other Precautions: EMPTY CONTAINERS RETAIN RESIDUE. DO NOT PRESSURIZE, CUT, WELD OR EXPOSE TO HEAT,

FLAME, STATIC ELECTRICITY, OR OTHER
SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN
SPRAYING OR USING IN CONFINED SPACES.

Ventilation:ADEQUATE TO KEEP