

CONCORDE BATTERY CORP -- BATTERY, DRY, P/N M15072/12001 -- 6140-00-195-5341
===== Product Identification =====

Product ID: BATTERY, DRY, P/N M15072/12001
MSDS Date: 04/09/1992
FSC: 6140
NIIN: 00-195-5341
MSDS Number: BPYDW
=== Responsible Party ===
Company Name: CONCORDE BATTERY CORP
Address: 2009 SAN BERNARDINO RD
City: WEST COVINA
State: CA
ZIP: 91790-1006
Country: US
Info Phone Num: 213-962-4006
Emergency Ph
one Num: 818-813-1234; NIGHTS 800-255-3924
CAGE: 63017

=== Contractor Identification ===
Company Name: CONCORDE BATTERY CORP
Address: 2009 SAN BERNARDINO RD
Box: City: WEST COVINA
State: CA
ZIP: 91790-1006
Country: US
Phone: 800-255-3924/818-813-1234
CAGE: 63017

===== Composition/Information on Ingredients =====

Ingred Name: LEAD OXIDE (SARA III)
CAS: 1314-41-6
Fraction by Wt: 60%
Other REC Limits: NONE SPECIFIED

Ingred Name: LEAD (SARA III)
CAS: 7439-92-1
RTECS #: OF7525000
Fraction by Wt:

38%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL RAT LD50 IS NOT KNOWN
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:PRODUCT ITSELF IS NONTOXIC. HOWEVER,
PRODUCT CONTAINS LEAD WHICH IS TOXIC. SOME LEAD COMPOUNDS ARE
LISTED AS CARCINOGENIC. CONTACT WITH THE LEAD IS HIGHLY UNLIKELY
AND ONLY BECOMES A FACTOR IN CASE OF FIRE OR PHYSICAL DAMAGE TO
BATTERY. SULFURIC ACID MUST BE ADDED BEFORE USE. SEE SULFURIC ACID
MSDS FOR ACID HAZARDS.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:FIRST AID IS GIVEN FOR LEAD DUST GENERATED WHEN HANDLING
DAMAGED BATTERIES. EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF
IRRITATION PERSISTS GET MEDICAL ATTENTION. SKIN: REMOVE
CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. IF SYMPTOMS
DEVELOP, GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR.
INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE
Extinguishing Media:THE PRODUCT ITSELF IS NONFLAMMABLE. USE MEDIA
APPROPRIATE FOR SURROUNDING FIRE, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:DO NOT USE WATER ON FIRES WHERE MOLTEN METAL
IS PRESENT. FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA TO PREVENT
THE POTENTIAL OF INHALING TOXIC FUMES.
Unusual Fire/Explosion Hazard:MOLTEN METALS PRODUCE FUMES AND/OR VAPORS
THAT MAY BE TOXIC OR RESPIRATORY IRRITANTS. THE PRODUCT CAN REACT
VIGOROUSLY WITH STRONG OXIDIZING AGENTS.

===== Accidental Release Measures =====

Spill Release Procedures:THIS PRODUCT

IS A DRY BATTERY AND IS
CONSIDERED AS NONSPILLABLE, IT IS PACKAGED ACCORDING TO 49CFR
PARAGRAPH 178.205 SPECIFICATION 12B. IN CASE OF AN ACCIDENT AND
CONTAINER IS BROKEN, PROTECTIVE GLOVES WILL BE REQUIRED TO HANDLE
THE BATTERY PARTS.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA. PROTECT FROM
PHYSICAL DAMAGE.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED UNDER NORMAL HANDLING.

Ventilation:NOT NORMALLY REQUIRED.

Protective Gloves:PROTECTIVE GLOVES FOR HANDLING PARTS.

Eye Protection:SAFETY GOGGLES FOR HANDLING PARTS.

Other Protective Equipment:NORMAL WORK CLOTHING.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

THIS NSN AND MSDS COVERS A DRY, LEAD/ACID BATTERY. SULFURIC ACID MUST

BE ADDED BEFORE USE OF THIS BATTERY. WHEN BATTERY IS BEING
ACTIVATED, SULFURIC ACID ADDED, SEE MSDS FOR SULFURIC ACID FOR
INFORMATION COVERING HAZARDS INVOLVED WHEN HANDLING SULFURIC ACID.

=====
===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:PLASTIC CASED DRY BATTERY. NO ODOR.

Percent Volatiles by Volume:NONE

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ST

STRONG OXIDIZERS.

Stability Condition to Avoid:EXTREMELY HIGH TEMPERATURE AND PHYSICAL DAMAGE.

Hazardous Decomposition Products:MOLTEN METALS PRODUCE FUMES AND/OR VAPORS THAT MAY BE TOXIC OR RESPIRATORY IRRITANTS.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE BATTERIES IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS FOR LEAD-ACID BATTERIES.

Disclaimer (provided w

ith this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.