

FARWEST PAINT MANUFACTURING CO -- EXTERIOR TRIM ENAMEL WHITE 27875 (LEAD AND --
8010-01-333-7762

=====
Product Identification
=====

Product ID:EXTERIOR TRIM ENAMEL WHITE 27875 (LEAD AND

MSDS Date:03/23/1992

FSC:8010

NIIN:01-333-7762

MSDS Number: BPYMZ

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD STREET

City:TUKWILA

State:WA

ZIP:98168

Country:US

In

fo Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

CAGE:2F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 S 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:2F266

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 4.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qt

y:1 LB

Ingred Name:TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 2.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 GRAMS/LITER

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: PROLONGED, IN CONFINED

AREAS MAY LEAD TO MUCOUS MEMBRANE IRRITAION, DIZZINESS, HEADACHE.

SKIN: IRRITATION OF SKIN. EYE: IRRITATION OF EYES. INGESTION:

AMOUNTS INGESTED INCIDENTAL TO CONSUM ER & INDUSTRIAL HANDLING NOT LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO KNOWN

CARCINOGENS IN REPORTABLE QUANTITIES AS DEFINED BY NTP, IARC, OSHA, OR EPA.

Medical Cond Aggravated by Exposure:NONE WHEN USED IN

ACCORDANCE WITH

SAFE HANDLING INSTRUCTIONS. SEE SAFE HANDLING AND USE INFORMATION.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS

DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY

WITH PLENTY OF WATER, THEN SOAP & WATER. REMOVE & WASH CONTAMINATED

CLOTHING BE FORE REUSE. EYE: FLUSH IMMEDIATELY WITHLARGE AMOUNTS OF

WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. OBTA

IN EMERG

MEDICAL TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MED TREATMENT

IMMEDIATELY

=====
===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, OR WATER FOG.

Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY

BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

=====
===== Accidental Release Measures =====

Spil

I Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED.

Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS IN INGREDIENTS.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF EXPOSURE TO MAT'L IS MAINTAINED BELOW TLV/PEL.

Protective Gloves:GLOVES RECOMMENDED BY G LOVE SUPPLIER.

Eye Protection:SFTY SPECTACLES W/UNPERFORATED SIDESHLDs

Other Protective Equipment:EYE WASH, SAFETY SHOWERS.

Work Hygienic Practices:KEEP WORK AREA CLEAN AND FREE FROM SPILLS AND LEAKS. ALWAYS WASH HANDS W/SOAP & WATER BEFORE HANDLING FOOD/DRINK/SMOKING

Supplemental Safety and Health

NOTE: THIS PRODUCT CONTAINS NO MERCURY IN REPORTABLE QUANTITIES AS DEFINED BY OSHA AND EPA.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F
,100C

Vapor Pres:23.8 @ 25C

Vapor Density:> AIR

Spec Gravity:9 TO 11 LBS/GAL

pH:7-8

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT.

Percent Volatiles by Volume:7.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS AND/OR HYDROFLUORIC ACID.

Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGEN

TS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.