

PRATT & LAMBERT, INC INDUSTRIAL COATINGS DIVISION -- LAC ACRYLIC N/C GLOSS WHITE
17875 -- 8010-00-527-2493

===== Product Identification =====

Product ID:LAC ACRYLIC N/C GLOSS WHITE 17875

MSDS Date:07/11/1991

FSC:8010

NIIN:00-527-2493

MSDS Number: BQCSN

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC INDUSTRIAL COATINGS DIVISION

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info

Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SOLVENT) (SARA III) (LFL 2.0, UFL 11.0)

CAS:110-19

-0
RTECS #:AI4025000
Fraction by Wt: 40%
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/ 700 MG/M3
ACGIH TLV:150 PPM/ 700 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SOLVENT) (SARA III) (LFL 2.0, UFL 13.0)
(VAPOR PRESSURE 33 MM HG @ 20C)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/STEL 500 PPM
ACGIH TLV:400 PPM/STEL 500 PPM

Ingred Name:NITROCELLULOSE (RESIN)
CAS:9004-70-0
RTECS #:QW0970000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOBUTYL ALCOHOL (SOLVENT) (SARA III) (LFL 1.0, UFL 11.0)
(VAPOR PRESSURE 10 MM HG @ 20C)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 200 CST
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT IN WATER
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:71

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES
OF IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING/ CUTTING: SMOKE, CO, CO2, OXIDES OF NITROGEN MAY BE
GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE & LOCAL LAWS.
INCINERATE IN EPA PERMITTED FACILITY. DONT INCINERATE CLSD CNTNR.
OBSERVE PRECAUTION FOR DISPOSAL OF FL

AMM MAT'L. DISPOSE CONTAM

ABSORB IN HZD WASTE LANDFILL. RCRA CLASSIFICATION WOULD BE D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.