

DEFT INC CHEMICAL COATING DIV -- CAT, MIL-C-85285B, 17925, 03W127ACAT -- 8010-01-285-3035
===== Product Identification =====

Product ID:CAT, MIL-C-85285B, 17925, 03W127ACAT
MSDS Date:07/31/1991
FSC:8010
NIIN:01-285-3035
Kit Part:Y
MSDS Number: BQDBF
=== Responsible Party ===
Company Name:DEFT INC CHEMICAL COATING DIV
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92714-6205
Country:US

Info

Phone Num:714-474-0400
Emergency Phone Num:800-424-9300 CHEMTREC
Preparer's Name:NORM GAUL
CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92614
Country:US
Phone:949-474-0400
CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:METHYL PROPYL KETONE (VAPOR PRESSURE 27.8 MM HG)
CAS:107-87-9
RTECS #:SA7875000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/STEL

250 PPM
ACGIH TLV:200 PPM/STEL 250 PPM

Ingred Name:ALIPHATIC ISOCYANATE (HEXAMETHYLENE DIISOCYANATE [HDI]
822-06-02, FREE MONOMER CONTENT LESS THAN 0.7 BASED ON RESIN)
CAS:28182-81-2
RTECS #:HQ9170000
Fraction by Wt: 45%
Other REC Limits:MOBAY TLV: 1 MG/M3

Ingred Name:METHYL ISOBUTYL KETONE (SARA III) (VAPOR PRESSURE 15 MM
HG)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANONE (SARA III) (VAPOR PRESSURE 3.4 MM HG)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 546 G/L
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IAR
C:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: RESP IRRIT, ACUTE NERV SYS
DEPRESSN (HEADACHE, DIZZINESS, STAGGERING, CONFUSION,
UNCONSCIOUSNESS, COMA). SKIN: ISOCYANATES REACT W/SKIN PROTEIN &
MOISTURE-IRRIT (SWELLING, REDNESS, RASH). EYES: IRRIT (TEARING,
REDNESS, SWELLING W/STING) ABSORPT: PROLONG/REPEAT: IRRIT, DRYING,
DEFATTING (SKIN CRACK). INGEST: **

Effects of Overexposure:** IRRIT, CORROSIVE TO MOUTH, STOMACH, DIGEST
TRACT. VOMIT: ASPIRATION OF SOLVENT TO L

UNGS, MAY RESULT IN CHEM

PNEUMONITIS. ACUTE: EYES, NOSE, THROAT IRRIT. INHAL: HEADACHE, DIFFICULT BREATHING, UNCON SCIOUSNESS. CHRONIC: PREV REPEAT OVEREXPOS/SINGLE LRG DOSE: SENSITIZATION (REACT TO LEVELS BELOW TLV).

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA AND DERMATITIS. ISOCYANATE SENSITIZATION.

=====
===== First Aid Measures =====

First Aid:INHAL: MOVE TO AREA FREE FROM RISK O F FURTHER EXPOSURE.

RESTORE BREATHING. ASTHMATIC TYPE SYMPTOMS MAY DEVELOP. GET MED AID. SKIN: REMOVE CONTAM CLOTHING. WASH AFFECTED AREA W/SOAP & WATER. WASH CONTA M CLOTHING BEFORE REUSE. EYES: FLUSH W/LUKEWARM WATER (LOW PRESSR) 15 MIN, LIFTING EYELIDS. GET MED AID. INGESTION: DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON. GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:46.0F

,7.8C

Lower Limits:1.1

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:FULL FIRE EQUIP W/SCBA,FULL PROTECT CLOTH.USE WATER TO COOL CLSD CNTNR(PREVNT PRESSR BLDUP,AUTOIGNIT,EXPLOS).HDI/IRRIT VAPOR GENERATED BY COMBUST/THERMAL DECOMP

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. KEEP FROM HEAT/IGNIT SOURCES. CLSD CNTNR MAY EXPLODE W/HEAT. APPL TO HOT SRFC S REQ PRECAUTION. OVEREXPOSURE DECOMP PROD MAY BE HEALTH HZD.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:MAY BE APPROPRIATE WHERE AIR MONITORING DEMONSTRATES VAPOR LEVELS BELOW TEN TIMES THE APPLICABLE EXPOSURE LIMITS.

Ventilation:EXHAUST VENT SUFFICIENT TO KEEP AIRBORNE CONCENTRATION OF SOLVENT, HDI & POLYISOCYANATES BELOW TLV. REMOVE IGNIT SOURCES

Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F

2

Boiling Pt:B.P. Text:213 TO 312F

Vapor Density:> AIR

Spec Gravity:0.95

Evaporation Rate & Reference:1.07 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:63.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:CONTACT WITH MOISTURE, MATERIALS WHICH

REACT WITH ISOCYANATES AND HIGH TEMPERATURES

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON

MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI

Conditions to Avoid Polymerization:CONTACT WITH MOISTURE, MATERIALS WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES

===== Disposal Considerations =====

Waste Disposal Methods:HAZARDOUS WASTE CHARACTERISTICS: IGNITABILITY:

YES. CORROSIVITY: NO. REACTIVITY: YES.

CTIVITY: YES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.