

FISKE BROTHERS REFINING CO -- LUBRIPLATE AERO -- 9150-00-068-6268

=====
Product Identification
=====

Product ID:LUBRIPLATE AERO

MSDS Date:01/01/1994

FSC:9150

NIIN:00-068-6268

MSDS Number: BQDGQ

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:800-255-3924 CHEMTEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

Contra

ct Num:SP0450-00-M-C855
CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:LITHIUM SOAP
Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL
Other REC Limits:NOT PROVIDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ADDITIVES
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:NOT PROVIDED
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Haza

rds Acute and Chronic:EFFECTS OF OVEREXPOSURE: PROLONGED OR
REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT ENTERING
THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM
PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS,
MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER
OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS
DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Explanation of Carcinogenic
ity:NONE

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE
SKIN IRRITATION. PRODUCT ENTERING THE EYES MAY CAUSE EYE
IRRITATION.

Medical Cond Aggravated by Exposure:NOT PROVIDED

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL
IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.
SKIN CONTACT: REMOVE ANY CONTAMINATED CLOTHING AND WASH WITH SOAP
AND WATER.

IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF APPEARANCE OR ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:190.6C, 375.F
Lower Limits:0.9 %
Upper Limits:7.0 %
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER SPRAY (FOG).
Fire Fighting Procedures:COOL FIRE EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.
Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.
Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.
Ventilation:LOCAL EXHAUST USED TO CAPTURE FUMES AND VAPORS.
Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.
Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.
Other Protective

ve Equipment:USE OIL-RESISTANT ARON, IF NEEDED.

Work Hygienic Practices:NOT PROVIDED

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Decomp Temp:Decomp Text:NOT PROVIDED

Vapor Pres:5(AIR=1)

Spec Gravity:0.884(H2O=1)

Viscosity:NOT PROVIDED

Evaporation Rate & Reference: