

SEYMOUR OF SYCAMORE,INC -- GREEN -- 8010-00-965-2392

=====  
Product Identification  
=====

Product ID:GREEN  
MSDS Date:09/14/1990  
FSC:8010  
NIIN:00-965-2392  
MSDS Number: BQDMV  
=== Responsible Party ===  
Company Name:SEYMOUR OF SYCAMORE,INC  
Address:917 CROSBY AVE  
City:SYCAMORE  
State:IL  
ZIP:60178-1343  
Country:US  
Info Phone Num:815-895-9101  
Emergency Phone Num:815-895-9101  
CAGE:59581  
=== Contractor Identif  
ication ===  
Company Name:SEYMOUR OF SYCAMORE  
Address:917 CROSBY AVE.  
Box:City:SYCAMORE  
State:IL  
ZIP:60178-1343  
Country:US  
Phone:815-895-9101/800-255-3924  
CAGE:59581

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TITANIUM DIOXIDE (AS DUST)  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 2.35%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293  
  
Ingred Name:ETHYL BENZENE (SARA III) (LEL: 1.20)  
CAS:100-41-4  
RTECS #:DA0700000  
F

raction by Wt: .20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/434 MG/M3  
ACGIH TLV:100 PPM/434 MG/M3  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PROPYLENE OXIDE (SARA III) (LEL: 2.80)  
CAS:75-56-9  
RTECS #:TZ2975000  
Fraction by Wt: .12%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:20 PPM; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III) (LEL: 1.27) (PEL CEILING: 300 PPM, MAX  
PEAK ABOVE CEILING [8HR] 5 MIN IN 2HR 10 MIN: 500 PPM)  
CAS:1  
08-88-3  
RTECS #:XS5250000  
Fraction by Wt: 18.21%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS (LEL: .70)  
CAS:64742-47-8  
Fraction by Wt: .85%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/525 MG/M3  
ACGIH TLV:100 PPM

Ingred Name:ISOPROPYL ALCOHOL (SARA III) (LEL: 2.00)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: .16%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/980 MG/M3  
ACGIH TLV:

400 PPM/985 MG/M3

Ingred Name:VARNISH MAKERS & PAINTERS NAPHTHA (LEL: 1.10)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 6.85%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM/1350 MG/M3

ACGIH TLV:300 PPM/1370 MG/M3

Ingred Name:DENATURED ETHYL ALCOHOL (TESCOL A) (LEL: 3.30)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 1.49%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM/1900 MG/M3

ACGIH TLV:1000 PPM/1880 MG/M3

Ingred Name:XYLENE (SARA III) (LEL: 1.00)

CAS:1330-20-7

RTECS #:ZE2100000

Fr

action by Wt: .83%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/435 MG/M3

ACGIH TLV:100 PPM/434 MG/M3

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SC-100 SOLVENT (LEL: 1.00)

CAS:64742-95-6

Fraction by Wt: .17%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:50 PPM/245 MG/M3

Ingred Name:ETHYLENE GLYCOL MONO BUTYL ETHER (SARA III) (LEL: 1.10)

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 1.10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PRO

PANE (LEL: 2.30)  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 18.0%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:1000 PPM/1800 MG/M3

Ingred Name:ISOBUTANE (LEL: 1.90)  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 12.0%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE OVEREXPOSURE; INHALATION:  
EXPOSURE TO SOLVENT VAPORS CONCENTRATION EXCEEDING THE ESTABLISHED  
THRESHOLD LIMIT VALUES CAN CAUSE RESPIRA  
TORY SYSTEM IRRITATION.  
INGEST: ACCIDENTAL INGESTION UNLIKELY . CHRONIC:  
SKIN: DEFATTING, LEADING TO IRRITATION AND DERMATITIS.  
Effects of Overexposure:SYMPTOMS OF OVEREXPOSURE ARE IRRITATION,  
HEADACHE, DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS AND  
ASPHYXIATION.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, BEGIN  
ARTIFICIAL RESPIRATION. SEEK IMMEDIATE MEDICAL ATTENTION. EYE:  
IMM  
EDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15  
MINUTES. GET MEDIC AL ATTENTION. SKIN: WASH WITH SOAP AND WATER.  
INGESTION: CALL A PHYSICIAN IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TOC  
Flash Point:NR  
Lower Limits:SEE INGRED  
Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL OR FOAM.  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE  
USED TO COOL CONTAINERS TO PREVENT BURSTING. IF WATER IS USE

D, FOG

NOZZLES ARE PREFERRED. WEAR GOGGLES & SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP WITH INERT MATERIAL AND PLACE IN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO

HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST. A SELF-CONTAINED BREATHING APPARATUS REQUIRED FOR CONCENTRATIONS ABOVE TLV LIMITS.

Ventilation:USE WITH ADEQUATE VENTILATION, SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS.

Protective Gloves:OPTIONAL

Eye Protection:ONLY WHERE SPRAY MIST GET IN EYES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:> AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING MATERIALS.

Stabili

ty Condition to Avoid:DO NOT STORE ABOVE 120 F. KEEP FROM SPARKS, PILOT LIGHTS OR OPEN FLAME.

Hazardous Decomposition Products:WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CO, CO2, HYDROGEN CHLORIDE VAPOR, TRACES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE AEROSOL. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PLACE AEROSOL CANS IN HOME COMPACTOR. DO NOT PUNCTURE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.