View NSN Online: https://aerobasegroup.de/nsn/5330-00-868-1129

Product ID:ASBESTOS FILLED SPIRAL WOUND GASKET MSDS Date:07/09/1986 FSC:5330 NIIN:00-868-1129 MSDS Number: BQKPZ === Responsible Party === Company Name: FLEXITALLIC GASKET CO.INC Address:8440 REMINGTON AVENUE Box:286 **City:PENNSAUKEN** State:NJ ZIP:08110 Country:US Info Phone Num:609 -486-4400 Emergency Phone Num:609-486-4400 CAGE:72433 === Contractor Identification === Company Name: ARCY MFG CO INC Address:3330 DELL AVE Box:City:NORTH BERGEN State:NJ ZIP:07047 Country:US Phone:201-319-9501 CAGE:4A760 Company Name: FLEXITALLIC GASKET CO.INC Address:8440 REMINGTON AVENUE Box:286 **City:PENNSAUKEN** State:NJ ZIP:08110 Country:US Phone:609-486-4400 CAGE:72433

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS # :CI6478500 Other REC Limits:NONE SPECIFIED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:NATURAL LATEX Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: PRODUCT IS NOT A HEALTH HAZARD UNDER ORDINARY CONDITIONS OF USE. DUST FR OM ABRASIVE ACTIONS (CUTTING, MACHINING, FILING, DRILLING, ETC.) MAY CONTAIN ASBESTOS FIBERS. CHRONIC OVEREXPOSURE TO AIRBORNE F IBERS MAY LEAD TO ASBESTOSIS, LUNG CANCER, MESOTHELIOMA. SMOKING WITH FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK. Explanation of Carcinogenicity: THIS PRODUCT CONTAINS ASBESTOS AND IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure: EYES: IRRITATION FROM AIRBORNE DUST. SKIN: MECHANICAL IRRITATION FROM D UST. INHALATION: INHALATION OF AIRBORNE DUST CONTAINING ASBESTOS FIBERS ON REPEATED EXPOSURE MAY CAUSE OR LEAD TO ASBESTOSIS, LUN G CANCER, MESOTHELIOMA. INGESTION: FREEASBESTOS FIBERS MAY BE A FACTOR IN CANCER OF THE GI TRACT AND LARNYX. Medical Cond Aggravated by Exposure: PERSON WITH PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED **RISK FROM EXPOSURE.**

First Aid:

EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: WASH AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. GET MEDICAL ATTENTION. INGESTION: INDUCE VOMITING. GET MEDICAL ATTENTION. OTHER: CHANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST PARTICLES INTO OTHER AREAS.

Extinguishing Media: USE MEDIA SUITABLE FOR SURROUNDING FIRE. WATER,

FOAM, CARBON DIOXIDE, DRY CHEMICALS. Fire Fighting Procedures:IF FIRE INVOLVES LARGE AMOUNTS OF PRODUCT, WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT DUE TO SMOKE AND POSSIBLE RELEASE OF ASBESTOS FIBERS. Unusual Fire/Explosion Hazard:PRODUCES SMOKE, SOME FUMES AND POSSIBLY SOME FREE ASBESTOS FIBERS WHEN BURNED.

Spill Release Procedures: USE PROPER PERSONAL PROTECTION. VACUUM OR WET CLEAN IF DUST

IS INVOLVED. ANY VACUUM SYSTEM SHOULD BE EQUIPPED WITH AN OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHERE. D O NOT DRY SWEEP OR USE COMPRESSED AIR. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN CLEAN DRY PLACE AWAY FROM INCOMPATIBLE MATERIAL. HANDLE IN A MANNER TO MINIMIZE FORMATION OR RETENTION OF AIRBORNE DUST.

Other Precautions: AS

MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO ABRASIVE ACTIONS AND DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED AND BECOME AIRBORNE.

Respiratory Protection:NONE REQUIRED UNDER NORMAL CONDITIONS OF USE. IF ANY OPERATIONS ARE PERFORMED ON THE PRODUCT THAT MAY RELEASE ASBESTOS FIBERS, USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS. Ventilation:NON

E REQUIRED UNDER NORMAL CONDITIONS OF USE. LOCAL EXHAUST

IS RECOMMENDED IN SITUATIONS WHERE DUST IS GENERATED.

Protective Gloves: NONE NORMALLY REQUIRED.

Eye Protection: SAFETY GLASSES/GOGGLES IF DUST GENERATED

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices: WASH AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. AVOID AIRBORNE DUST GENERATION.

Supplemental Safety and Health

CHANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST PARTICLES INTO OTHER AREAS. S

MOKING ALONG WITH ASBESTOS FIBER INHALATION GREATLY INCREASES CANCER RISK.

HCC:T6 Spec Gravity:2.5 Solubility in Water:NEGLIGIBLE Appearance and Odor:LIGHT BLUE. NO ODOR. Stability Indicator/Materials to Avoid:YES AVOID STORAGE WITH STRONG OXIDIZING AGENTS. DIRECT FLAME WILL IGNITE BINDER. Stability Condition to Avoid:STABLE UNDER NORMAL CONDITIONS OF STORAGE AND USE. Hazardous Decomposition Products: IN A FIRE, SMOKE, CARBON MONOXIDE RELEASED UNDER CERTAIN CONDITIONS. ASBESTOS FIBERS MAY BE RELEASED ONCE BINDER BURNED. Conditions to Avoid Polymerization: WILL NOT OCCUR. Waste Disposal Methods: DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS, USE LANDFILLS APPROVED F OR ASBESTOS DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility fo r the suitability of this information to their

particular situation.