

MOBIL OIL CORP -- DIESEL FUELS -- 9140-00-286-5294

===== Product Identification =====

Product ID:DIESEL FUELS

MSDS Date:01/12/1989

FSC:9140

NIIN:00-286-5294

MSDS Number: BQMBY

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-227-0707 X3265

Emergency Phone Num:609-737-4411 800-424-9300(CHEMTREC)

Prepa

rer's Name:ENV. HEALTH&SAFETY DEPT.

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL (NO. 2 DIESEL)

CAS:68334-30-5

Fraction by Wt: MAJOR

Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYCYCLIC AROMATIC HYDROCARBONS

Fracti

on by Wt: TRACE
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:LD50 ORAL RAT=9G/KG[RTECS];TWA=100PPM
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN:SLIGHT IRRITANT.DERMALLY
NON-TOXIC.INHAL:IRRITANT.INGEST:SLIGHTLY TOXIC.ASPIRATION
HAZARD.SLIGHTLY TOXIC.EYES:EXPECTED TO BE
NON-IRRITATING.CHRONIC:TRACE POLYCYCLIC
AROMATIC HYDROCARBONS ARE
SUSP ECTED CARCINOGENS.
Explanation of Carcinogenicity:RTECS 92-4 HAS MONOGRAPHS SHOW DIESEL
FUEL AS A TUMORIGEN.MANUFACTURER LINKS DIESEL FUEL TO LUNG CANCER.
Effects of Overexposure:INHAL:DIZZINESS,NAUSEA,UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:MATERIEL MAY CONTAIN TRACES OF
POLYCYCLIC AROMATIC HYDROCARBONS[PCAH].WITH POOR HYGIENE AND
PROLONGED EXPOSURE,SKIN CANCER MAY DEVELOP.

=====
===== First Aid Measures =====
=====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.SEE DOCTOR.
SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH WITH SOAP AND
WATER.SEE DOCTOR. INHALATION: REMOVE VICTIM TO FRESH AIR.GIVE
OXYGEN/CPR IF NEEDED.SEE DOCTOR. INGESTION: DO NOT INDUCE
VOMITING.ADMINISTER VEGETABLE OIL.GET PROMPT QUALIFIED MEDICAL
HELP.CAUTION:LUNG DAMAGE CAN RESULT FROM VOMITING.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:PMCC
Flash
Point:100F,38C
Autoignition Temp:Autoignition Temp Text:494F
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. HMIS
SUGGESTS DO NOT USE WATER STREAM. IT MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTIBLE MATERIEL.VAPORS HEAVIER THAN
AIR. MAY TRAVEL ALONG GROUND AND FLASHBACK. CONTAINERS EXPOSE

D TO
FIRE MAY IGNITE EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures: ADSORB ON FIRE RESISTANT TREATED SAWDUST OR
DIATOMACEOUS EARTH. SHOVEL INTO A CONTAINER FOR DISPOSAL. NOTIFY
CHEMTREC AT 800-424-9300 IF SPILLS IN WATERWAY.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED
PLACE, AWAY FROM HEAT, IGNITION SOURCES AND INCOMPATIBLE
MATERIALS.

KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions: AVOID BREATHING VAPORS, AND EYE AND SKIN CONTACT. USE
ONLY WITH ADEQUATE VENTILATION. DO NOT SIPHON BY MOUTH. BOND AND
GROUND CONTAINERS DURING TRANSFER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE NORMALLY REQUIRED WITH ADEQUATE
VENTILATION. NIOSH/MSHA RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE
APPROPRIATE FOR EXPOSURE OF CONCERN OR SCBA IF TLV IS EXCEEDED.

Ventilation:

SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST
VENTILATION IN CONFINED SPACES. USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves: NEOPRENE.

Eye Protection: GOGGLES.

Other Protective Equipment: FULL BODY LONG-SLEEVED GARMENTS TO PREVENT
REPEATED OR PROLONGED SKIN CONTACT. EYE WASH STATION AND SAFETY
SHOWER.

Work Hygienic Practices: AVOID CONTACT WITH EYES AND SKIN. DO NOT
BREATHE VAPORS. WASH THOROUGHLY AFTER HANDLING. LAUNDER
CONTAMINATED CLOTHING.

Supplemental Safety and
Health

THESE PRECAUTIONS ARE FOR NORMAL USES AND CONDITIONS. WHERE SPECIAL OR
UNUSUAL CONDITIONS EXIST, CONSULT AN INDUSTRIAL HYGIENIST.

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: >300F, >149C

Vapor Pres: 0.5

Spec Gravity: .82-.87

Solubility in Water: NEGLIGIBLE

Appearance and Odor: LIQUID; CLEAR TO AMBER; CHARACTERISTIC HYDROCARBON
ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to

Avoid: YES

HALOGENS, STRONG ACIDS, ALKALIES, STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION (EG. STATIC ELECTRICITY BUILDUP).

Hazardous Decomposition Products: DIESEL ENGINE EXHAUST: CO, NITROGEN COMPOUNDS, OXIDES OF SULFUR, HYDROCARBONS (GASES AND PARTICULATES).

===== Disposal Considerations =====

Waste Disposal Methods: MATERIEL IS SUITABLE FOR BURNING FOR FUEL VALUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.