

DESOTO AEROSPACE COATINGS, INC -- PRIMER GREEN LOW IR 515X370 -- 8010-01-048-6539
===== Product Identification =====

Product ID:PRIMER GREEN LOW IR 515X370

MSDS Date:02/12/1991

FSC:8010

NIIN:01-048-6539

Kit Part:Y

MSDS Number: BQMJM

=== Responsible Party ===

Company Name:DESOTO AEROSPACE COATINGS, INC

Address:1608 FOURTH STREET

City:BERKELEY

State:CA

ZIP:94710

Country:US

Info Phone Num:818-549-78

23

Emergency Phone Num:800-424-9300(CHEMTREC)/800-228-5635

CAGE:DESOT

=== Contractor Identification ===

Company Name:DESOTO AEROSPACE COATINGS, INC

Address:1608 FOURTH STREET

City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:818-549-7822

CAGE:DESOT

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

Box:City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

===== Composition/Information on Ingredients =====

==

Ingred Name:NON-HAZARDOUS ADDITIVES, RESIN AND PIGMENTS

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL N-AMYL KETONE (VAPOR PRESSURE 2.1 MM HG)

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

Ingred Name:TOLUENE (VAPOR PRESSURE 22 MM HG) (SARA 313)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:STRONTIUM CHROMATE (SARA 313)

CAS:7789-06-2

RTECS #:GB3240000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.1 PPM CRO3;CEILING

ACGIH TLV:0.0005MG CR/M3;A2;93

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:IRON OXIDE

CAS:1332-37-2

RTECS #:NO7380000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIF

IED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

Ingred Name:METHYL ETHYL KETONE (VAPOR PRESSURE 74.9 MM HG) (SARA 313)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TALC NON-ASBESTIFORM
CAS:14801-96-6
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2 (RESPIR)
ACGIH TLV:2 (RESPIR)

Ingred Name:CRYSTALLINE SILICA-QUARTZ
CAS:14808-60-7
RTECS #:VV73
30000
Fraction by Wt: < 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:VOC: 5.14 (GRAMS/LITER)
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES
Health Hazards Acute and Chronic:INHAL: NASAL/RESP IRRIT AND ACUTE CNS
DEPRESS W/HEADACHE-DIZZINESS-STAGGERING
GAIT-CON

FUSION-UNCONSCIOUSNESS. ASPHYXIATION FROM BREATHING OXYGEN DEFICIENT AIR. SKIN: IRRIT-DEFAT- DERMATITIS. EYE: IRRIT. INGEST: GASTROINTESTINAL IRRIT-NAUSEA-VOMITING- DIARRHEA. ASPIR OF MATL INTO LUNGS MAY CAUSE CHEM PNEUMONITIS-FATAL.

Explanation of Carcinogenicity:HEXAVALNT CHROMIUM COMPOUND AND CRYSTALLINE SILICA ARE LISTED AS CARCINOGENS BY IARC AND NTP.

Effects of Overexposure:PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. CONCENTRATION DIFFICULTIES-DIMINISHED ACTUAL DEXTERITY-MEMORY LOSS.

LIVER- KIDNEYS-LUNG-SPLEEN DAMAGE. SILICOSIS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN, LUNG AND EYE CONDITIONS

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR FROM EXPOSURE. GIVE ARTIFICIAL RESPIRATION OR CPR IF REQUIRED. IF BREATHING IS DIFFICULT, GIVE OXYGEN. KEEP WARM AND QUIET. GET MED ATTN. SKIN: WASH AFFECTED AREAS WITH SOAP AND WATER. DO NOT USE SOLVENTS. REMOVECONTAMINATED CLO

THING-WASH BEFORE REUSE. GET MED ATTN. EYE: FLUSH WITH WATER 15 MINS. GET MED ATTN- PREFERRABLY FROM AN OPHTHALMOLOGIST. INGEST: GET MED ATTN

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:22.0F,-5.6C

Lower Limits:1.11%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE-COOL FIRE EXPOS CNTNR W/WTR. FOG NOZZLES PREFERRED. WEAR NIOSH/MSHA SCBA AND PROTECTIVE CLO

THING TO PREVENT CONTACT W/SKIN & EYES

Unusual Fire/Explosion Hazard:VAPORS MAY ACCUMULATE IN POOR VENT/CONFINED AREAS. VAPORS FORM EXPLOS MIX W/AIR-MAY TRAVEL DISTANCES. FLASHBACK/FLAME TO HNDLING SITE. CLSD CNTNR EXPLODE W/HEAT

=====
===== Accidental Release Measures =====

Spill Release Procedures:DEPEND ON QTY-CIRCUMSTANCES, REPORTABLE UNDER FED LAW. CK W/STATE/LOCAL GOVT. RMV IGNIT SRCS. WEAR PERSONAL PROTECT EQUIP-AVOID BREATH VAPORS-SKIN/EYE CONT

ACT. NON-SPARK

TOOLS. EXCESS QTY-USE EMER RES PONSE PROFESSIONAL. SM: DIKE/ABSORB
W/INERT MATL

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CNTNR CLSD TIGHT-AWAY FROM
HEAT-IGNIT SRCS. DONT STORE >49C. STORE FLAMM LIQ IN ACCORD W/NFPA.
FOLLOW GROUND/BOND REQ W/TRANS-AVOID LIQ FREE FALL

Other Precautions:EMPTY DRUMS HOLD EXPLOS VAPORS. DONT
CUT-PUNCTURE-WELD ON/NEAR DRUM. DONT INGEST-INHAL CONC VAPORS.
PREVENT P

ROLONG CONTACT W/ CONTAM CLOTH-WASH BEFORE REUSE. VAPORS
COLLECT IN LOW/CONFINED AREA. FOLL OW ALL APPROP PROCED BEFORE
ENTERING ARE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:TLVS EXCEEDED OR SPRAY MIST-USE NIOSH/MSHA
RESPIRATORY PROTECTION FOR INDICATED COMPONENTS. CONFINED
AREAS-NIOSH/MSHA AIR SUPPLIED RESPIRATORS. FOLLOW RESPIRATOR MFR
DIRECTIONS AND OSHA REGULATIONS (2 9 CFR 1910.134) FOR RESPIRATOR
USE.

Ventilation:G

ENERAL DILUTION/LOCAL EXHST IN VOL/PATTRN TO KEEP LEVEL
BELOW TLV OR PEL LIMIT. UNEXPOSED: KEEP LEVEL BELOW 25% OF LEL

Protective Gloves:CHEMICALLY RESISTANT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER
PROTECTIVE CLOTHING. A SAFETY SHOWER-EYE BATH-WASHING FACILITIES
SHOULD BE AVAILABLE

Supplemental Safety and Health

KEY1;F3.DO NOT SMOKE WHERE THIS MATERIAL IS USED OR STORED. DO NOT
APPLY TO HOT SURFACES.

=

=====
===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:175-300F

Vapor Density:> THAN AIR

Spec Gravity:1.28

Evaporation Rate & Reference:SLOWER THAN N-BUTYL AC

Appearance and Odor:GREEN LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:61.3%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS
INCLUDING CARBON MONOXIDE A

ND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:ENSURE MATL IS PACKAGED-STORED-TRANSPORTED AND OTHERWISE MANAGED IN ACCORD W/LOCAL-STATE AND FEDERAL REGULATIONS. NO DISPOSAL METHOD IS TO BE USED THAT WOULD POSE ENVIRONMENTAL/HUMAN HEALTH THREAT INC LUD ANY WHICH WOULD CONTAMINATE GROUND/SURFACE WTR

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.