View NSN Online: https://aerobasegroup.de/nsn/6830-01-111-8264

Product ID:MSA P/N 473583 STEEL CYLINDER AND VALVE ASS MSDS Date:03/01/1990 FSC:1045 NIIN:01-111-8264 **MSDS Number: BQMKN** === Responsible Party === Company Name: MINE SAFETY APPLIANCES CO Address:3880 MEADOWBROOK RD City:MURRYSVILLE State:PA ZIP:15668-1753 Country:US Info P hone Num:412-325-1313 Emergency Phone Num:412-325-1313 CAGE:55799 === Contractor Identification === Company Name: MINE SAFETY APPLIANCES CO DBA MSA Address:3880 MEADOWBROOK RD Box:City:MURRYSVILLE State:PA ZIP:15668-1753 Country:US Phone:724-733-9272 CAGE:55799 Ingred Name:OXYGEN

CAS:7782-44-7 RTECS #:RS2060000 Fraction by Wt: 21% % Other REC Limits:NONE SPECIFIED

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Fraction by Wt: 79% % Other REC Limits:NONE SPECIFIED ACGIH TLV:ASPHYXIANT; 9192

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT APPLICABLE. Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: PHYSICAL INJURY DUE TO RUPTURE/ EXPLOSION OF CONTAINER. INJECTION OF COMPRESSED AIR INTO THE BLOOD STREAM. Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN. Effects of Overexposure:NONE Medical Cond Aggravated by Exposure:NONE First Aid:GET IMMEDIATE MEDICAL CARE FOR THOSE INJURED BY EXPLODING CYLINDERS OR IF AIR IS SUSPECTED TO HAVE BEEN INJECTED INTO THE **BLOOD STREAM.** Flash Point:NON-FLAMMABLE Extinguishing Media: PRODUCT IS NON FLAMMABLE. EXTINGUISH FIRE WITH MEDIA APPRO PRIATE FOR SOURCE OF FIRE. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: CONTAINS AIR UNDER 2200 PSI. CONTAINERS EXPOSED TO HEAT MAY RUPTURE OR EXPLODE. 

Spill Release Procedures:NONE Neutralizing Agent:NOT APPLICABLE.

====== Handling and Storage =====

Handling and Storage Precautions:PROTECT CYLINDERS FROM PHYSICAL DAMAGE. STORE AWAY FROM EXTREME HEAT (BELOW 125F). KEEP CYLINDER VALVES CLOSED WHEN NOT IN USE AND WHEN EMPTY.
Other Precautions:DO NOT DEFACE CYLINDERS OR LABELS. USE ALL RECOMMENDED SAFETY PROCEDURES WHEN HANDLING CYLINDERS. READ AND OBEY ALL INSTRUCTIONS ON LABEL.

======= Exposure Controls/Personal Protection ===============

Protective Gloves:WORK GLOVES FOR HANDLING CYLINDERS. Eye Prot ection:APPROVED SAFETY GLASSES OR FACE SHIELD. Other Protective Equipment:SAFETY SHOES AND HEARING PROTECTION. Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. USE PROPER CARE WHEN HANDLING AND STORING CYLINDERS. Supplemental Safety and Health THIS IS BREATHING AIR.

HCC:G3 Boiling Pt:B.P. Text:-318F,-194C Vapor Density:1.0 Solubility in Water:1.87% Appearance and Odor:COLORLE SS, ODORLESS GAS Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES NOT RELAVENT Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES Hazardous Decomposition Products:NONE

Waste Disposal Methods:RELEASE PRESSURE SAFELY BEFORE DISPOSAL OF CYLINDER. DISPOSEMUST BE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.