

UNION CARBIDE CORP LINDE DIV -- NITROGEN -- 6685-00-292-3688

===== Product Identification =====

Product ID:NITROGEN

MSDS Date:08/01/1985

FSC:6685

NIIN:00-292-3688

MSDS Number: BQNDN

=== Responsible Party ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:203-744-3487

Emergency Phone Num:800-822-4357

CAGE:36346

==

= Contractor Identification ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

Company Name:WEKSLERIGLASS THERMOMETER CORP

Address:80 MILL ROAD

Box:City:FREEPORT

State:NY

ZIP:11520

Country:US

Phone:516-623-0100

CAGE:64467

===== Composition/Information on Ingredients =====

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fraction by Wt: 100%

ACGIH TLV:AS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGESTION: PRODUCT IS A GAS AT NORMAL  
TEMPERATURE AND PRESSURE. SKIN: NO HARMFUL EFFECT EXPECTED FROM  
VAPOR. INHALATION: ASPHYXIANT. EYE: NO HARMFUL EFFECTS EXPECTED  
FROM VAPOR.

Explanation of Carcinogenicity:NOT A CARCINOGEN.

Effects of Overexposure:INHALATI

ON: MODERATE CONCENTRATIONS MAY CAUSE  
HEADACHE, DROWSINESS, DIZZINESS, EXCITATION, EXCESS SALIVATION,  
VOMITING, AND UNCONSCIOUSNESS. LACK OF OXYGEN CAN CAUSE DEATH.  
CONTACT WITH LIQUID MAY CAUSE FROSTBITE.

Medical Cond Aggravated by Exposure:DOES NOT SUGGEST THAT OVEREXPOSURE  
IS LIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

=====  
===== First Aid Measures =====

First Aid:SWALLOWING-THIS PRODUCT IS A GAS AT NORMAL TEMPERATURE &  
PRESSURE. SK  
IN-IMMEDIATELY WARM FROSTBITE AREA WITH AWARM WATER. IF  
MASS EXPOSURE, REMOVE CLOTHING WHILE SHOWERING W/WARM WATER. CALL A  
PHYSICI AN. INHALATION-REMOVE TO FRESH AIR. GIVE CPR IF NOT  
BREATHING. GIVE OXYGEN IF HARD TO BREATH. CALL A PHYSICIAN.  
EYE-IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MIN. SEE A  
PHYSICIAN IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point:NA

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:NITROGEN CANNOT  
CATCH FIRE. USE MEDIA APPROPRIATE  
FOR SURROUNDING FIRE.

Fire Fighting Procedures:EVACUATE ALL PERSONNEL FORM DANGER AREA.  
IMMEDIATELY DELUGE CONTAINERS W/WATER SPRAY FROM MAX DISTANCE UNTIL  
COOL, THEN MOVE CONTNR AWAY FROM FIRE AREA W/O RISK

Unusual Fire/Explosion Hazard:CONTAINER MAY RUPTURE DUE TO HEAT OF  
FIRE. NO PART OF CONTAINER SHOULD BE SUBJECTTO TEMPERATURE HIGHER  
THAN 52C (APPRX. 125F). GAS CANNOT CATCH FIRE.

=====  
===== Accidental Release Measures =====

=====

Spill Release Procedures:USE SCBA WHERE NEEDED. SHUTOFF LEAK IF W/O RISK. VENTL AREA OF LEAK OR MOVE CONTAINER TO WELL VENTLAREA. EVACUATE ALL PERSONNEL FROM DANGER AREA. TEST AREA FOR SUFFICIENT OXYGEN CONTENT PRIOR TO PERMI TTING RE-ENTRY OF PERSONNEL.

===== Handling and Storage =====

Handling and Storage Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN SYSTEM BY VENTING TO SAFE PLACE, THEN REPAIR THE LEAK.

Other Precautions:HIGH PRESSURE GAS. CAN CAUSE RAPID SUFFOCATION DUE TO OXYGEN DEFICIENCY. STORE AND USE WITH ADEQUATE VENTILATION. CLOSE VALVE WHEN NOT IN USE AND WHEN EMPTY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT ACCORDANCE WITH OSHA 29 CFR 1910.134. RESPIRATORS SHALL BE ACCEPTABLE TO MSHA AND NIOSH.

Ventilation:LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE Protective Glo

ves:PREFERRED FOR CYLINDER HANDLING

Eye Protection:ACCORDANCE WITH OSHA 29 CFR 1910.133

Other Protective Equipment:METATARSAL SHOES FOR CYLINDER HANDLING.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-320F,-196C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Pres:GAS

Vapor Density:0.967

Spec Gravity:GAS

Evaporation Rate & Reference:NA

Solubility in

Water:NEGLIGIBLE

Appearance and Odor:COLORLESS, ODORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

UNDER CERTAIN CONDITIONS, NITROGEN CAN REACT VIOLENTLY WITH LITHIUM, NEODYMIUM, TITANIUM, OZONE.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

=====

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT RESIDUE, DISPOSABLE CONTAINER/LINER IN COMPLIANCE WITH FEDERAL, LOCAL, AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.