View NSN Online: https://aerobasegroup.de/nsn/9140-00-286-5294

SINCLAIR MARKETING INC -- LIGHT FUEL OIL (DIESEL) -- 9140-00-286-5294

Product ID:LIGHT FUEL OIL (DIESEL) MSDS Date:01/01/1992 FSC:9140 NIIN:00-286-5294 **MSDS Number: BQNPX** === Responsible Party === Company Name: SINCLAIR MARKETING INC Address:550 EAST SOUTH TEMPLE Box:31825 City:SALT LAKE CITY State:UT ZIP:84131 Country:US Info Phone Num:801-363-5100 **Emergency Phon** e Num:801-363-5100 CAGE:5X969 === Contractor Identification === Company Name: SINCLAIR MARKETING INC Address:550 EAST SOUTH TEMPLE Box:31825 City:SALT LAKE CITY State:UT ZIP:84131 Country:US Phone:801-363-5100 CAGE:5X969

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 0.1-1.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHALENE (SARA III) CAS:91-20-3 RTECS #:QJ0525000 Fraction by Wt: 2-12.5% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM/15 STEL ACGIH TLV:10 PPM/15 STEL; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS
======================================
LD50 LC50 Mixture:ORAL LD50 (RAT) IS 7.5 G/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE-CONTACT MAY C AUSE IRRITATION. SKIN-CONTACT MAY IRRITATE OR BURN SKIN. ABSORPTION THROUGH THE SKIN MAY CAUSE SYMPTOMS OF INTOXICATION, FOLLOWED BY KIDNEY DAMAGE. INGESTION-ASPIRATION MAY RESULT IN SEVERE LUNG DAMAGE & PULMONARY EDEMA, NERVOUS SYSTEM DEPRESSION OR EXCITEMENT. Explanation of Carcinogenicity:IARC HAS CONCLUDED THAT THERE IS
INADEQUATE EVIDENCE FOR THE CARCINOGENICITY IN HUMANS OF DIESEL
FUEL. Effects of Overexposure:INHALATION-OVEREXPOSURE MAY CAUSE WEAKNESS, HEADACHE , DROWSINESS, CONFUSION, BLURRED VISION, OR NAUSEA; GREATER EXPOSURE MAY CAUSE DIZZINESS, IRREGULAR HEARTBEAT, COMA, COLLAPSE & DEATH. INGESTION-NAU SEA, VOMITING, DIARRHEA AND ABDOMINAL PAIN MAY OCCUR. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:EYE-FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES MINIMUM. SEEK MEDICAL ATTENTION PROMPTLY. SKIN-DISCARD CONTAMINATED LEA
THER ARTICLES. WASH CONTACT AREAS WITH SOAP & WATER. INGESTION-DO NOT IN DUCE VOMITING. GET MEDICAL ASSISTANCE PROMPTLY. INHALATION-REMOVE FROM FUTHER EXPOSURE. IF UNCONSCIOUSNESS OCCURS, SEEK IMMEDIATE MEDICAL ASSISTANCE.
======================================
Flash Point:100F TO 190F Autoignition Temp:Autoignition Temp Text:350F Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG, VAPORIZING LIQUID (HALON). Fire Fighting Procedures:

FIRE FIGHTING SHOULD USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES, & FULL PROTECTIVE EQUIPMENT (BUNKER GEAR). COOL ADJACENT STRUCTURES AND DRUMS. Unusual Fire/Explosion Hazard:VAPORS WILL BE RELEASED ABOVE FLSAH POINT & WHEN MIXED WITH AIR, CAN BURN OR EXPLODE IN CONFINED SPACE IF EXPOSED TO SOURCES OF IGNITION.
======================================
Spill Release Procedures:TREAT SPILL AS AN OIL SPILL. REPORT SPILLS. ELEMINATE IGNI TION SOURCES. REMOVE LEAKING CONTAINERS TO A SAFE AREA. CONTAIN & REMOVE BY MECHANICAL MEANS. GUARD AGAINST CONTAMINATION OF WATER SUPPLIES.
======================================
 Handling and Storage Precautions: STORE AWAY FROM IGNITION SOURCES IN A COOL AREA. OUTSIDE OR DETACHED STORAGE IS PREFERRED. USE NON-SPARKING TOOLS & EQUIPMENT. USE ONLY AS FUEL. Other Precautions: GROUND & BOND ALL TRANSFER & STORAGE EQUIPMENT. DRUMS MUST BE GROUNDED/BO NDED/EQUIPPED WITH SELF-CLOSING VALVES, PRESSURE VACUUM BUNGS, & FLAME ARRESTORS. DO NOT USE AS A CLEANER OR SOLVENT. DO NOT SI PHON BY MOUTH.
======================================
Respiratory Protection:APPROVED RESPIRATORY PROTECTION MUST BE USED WHEN VAPOR OR MIST CONCENTRATIONS ARE UNKOWN OR EXCEDD THE TLV. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS OR MISTS. Ventilation:NONE SPECIFIED BY MANUFACTURER. Protective Gloves:IMPERVIOUS GLOVES. Eye Protection:FULL FACE SHIELD, CHEMICAL GOGGLES. Other Protective Equipment:IMPERVIOUS GLOVES, BOOTS & WHOLE BODY PROTECTION. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Work Hygienic Practices:WASH THOROUGHLY AFTER USE. Supplemental Safety and Health NOTE TO PHYSICIAN: MATERIAL IF ASPIRATED INTO THE LUNGS MAY CAUSE CHEMICAL PNEUMONITIS. TREAT APPROPIATELY.

HCC:F4 Vapor Pres: