

ASHLAND CHEMICAL, INC. SUBS. OF ASHLAND OIL, INC. -- TRICHLOROETHANE 111 DEGREASE  
COLD/VAPOR -- 6810-00-664-0388

===== Product Identification =====

Product ID:TRICHLOROETHANE 111 DEGREASE COLD/VAPOR

MSDS Date:07/14/1989

FSC:6810

NIIN:00-664-0388

MSDS Number: BQNQT

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL, INC. SUBS. OF ASHLAND OIL, INC.

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Coun

try:US

Info Phone Num:614-790-3333

Emergency Phone Num:800-274-5263

CAGE:5A188

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO

Address:5200 PAUL BLAZEL MEMORIAL PARKWAY

Box:City:DUBLIN

State:OH

ZIP:43017

Country:US

Phone:614-889-4505

CAGE:5A188

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: >95%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450ST

EL:9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingrid Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)  
CAS:123-91-1  
RTECS #:JG8225000  
Fraction by Wt: 2.5%  
OSHA PEL:S, 100 PPM  
ACGIH TLV:S, 25 PPM; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 10300 MG/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OS  
HA:NO  
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE EYE & SKIN  
IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CENTRAL NERVOUS  
SYSTEM DEPRESSANT. LOSS OF CONSCIOUSNESS AND EVEN DEATH CAN OCCUR  
AT HIGH LEVELS OF EXPOSURE.  
Explanation of Carcinogenicity:1,4-DIOXANE IS LISTED AS AN ANIMAL  
CARCINOGEN BY NTP AND IARC.  
Effects of Overexposure:INCOORDINATION AND IMPAIRED JUDGMENT MAY OCCUR  
AT VAPOR EXPOSURES FROM 500-1000 PPM. DIZZINESS, DROWSINESS, AND  
GENERAL ANESTETHI  
C EFFECTS MAY OCCUR IN RANGES OF 1000 PPM AND  
HIGHER.  
Medical Cond Aggravated by Exposure:INCREASED SENSITIVITY TO ADRENALIN  
MAY BE CAUSED BY OVER EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR.  
IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYE:  
FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET  
MEDICAL AT TENTION. SKIN: REMOVE CONTAMINATED CLOTHI

NG. WASH WITH

SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING. GIVE MILK OR USP MINERAL OIL. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Lower Limits:7.5%

Upper Limits:15.0%

Extinguishing Media:WATER FOG

Fire Fighting Procedures:WATER MAY BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL UNTIL FIRE IS OUT. WEAR SCBA WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE.

Unusual Fire/Explosion Hazard:N

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM BECAUSE PRODUCT CAN IGNITE EXPLOSIVELY(EVEN JUST RESIDUE)

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE UP WITH RAGS OR TOWELS. LARGE SPILLS: WEAR NIOSH APPROVED RESPIRATOR. VENTILATE AREA. DIKE TO RETAIN FLUID. PUMP UP FREE LIQUID. RESIDUE WILL EVAPORATE QUICKLY. DO NOT FLUSH TO SEWER OR WATERWAY.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:DO NOT USE WITH ALUMINUM. READ AND FOLLOW DIRECTIONS ON LABEL. DO NOT REUSE CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN HIGH VAPOR AREA, USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. USE SELF-CONTAINED

BREATHING APPARATUS IF VAPOR LEVELS EXCEED 1000 PPM.

Ventilation:LOCAL EXHAUST RECOMMENDED TO CONTROL VAPORS BELOW 50% OF TLV.

Protective Gloves:NEOPRENE, PVA GLOVES RECOMMENDED.

Eye Protection:USE CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE. EYE WASH STATION & SAFETY SHOWER RECOMMENDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING, SMOKING OR USING TOILET FACILITIES. DO NOT BREATHE

VAPORS OR MIST.

Supplemental Safety and Health

TARGET ORGANS ARE SKIN, CNS, CVS, AND EYES

===== Physical/Chemical Properties =====

HCC:T4

Boiling Pt:B.P. Text:161F,72C

Vapor Pres:100 MM HG

Vapor Density:4.5(AIR=1)

Spec Gravity:1.3-1.324

Evaporation Rate & Reference:2.6 (ETHLY ETHER=1)

Appearance and Odor:HOMOGENEOUS SOLUTION THAT IS CLEAR. APHA COLOR 15  
MAX.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, REACTIVE METALS SUCH AS ALUMINU;M AND MAGNESIUM.

Stability Condition to Avoid:OPEN FLAMES, WELDING ARCS, RESISTANCE  
HEATERS, ETC., WHICH CAN RESULT IN THERMAL DECOMPOSITION.

Hazardous Decomposition Products:WHEN INVOLVED IN FIRE,  
1,1,1-TRICHLOROETHANE EMITS HIGHLY TOXIC AND IRRITATING HYDROGEN  
CHLORIDE AND PHOSGENE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISOPSE OF I/A/W FED  
ERAL, STATE & LOCAL  
REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this inf  
ormation to their  
particular situation.