

DAVLIN PAINT CO. -- 100 COVERBRITE: TB -- 8010-00-045-3478

=====
Product Identification
=====

Product ID:100 COVERBRITE: TB

MSDS Date:03/20/1992

FSC:8010

NIIN:00-045-3478

MSDS Number: BQQCV

=== Responsible Party ===

Company Name:DAVLIN PAINT CO.

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Info Phone Num:510-848-2863

Emergency Phone Num:800-424-9300

Preparer's Name

:PATRICIA SHAW

CAGE:DO185

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

Company Name:DAVLIN PAINT CO.

Address:P.O. BOX 2308

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Phone:415-889-7098

CAGE:DO185

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Hazards Identification
=====

=====
LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE IRRITATION OR RASH UPON PROLONGED OR REPEATED CONTACT. INHALATION: VAPORS OR MISTS CAN CAUSE NOSE AND THROAT IRRITATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, OR DIARRHEA.

Explanation of Car

cinogenicity:CRYSTALLINE SILICA IS LISTED BY IARC AS A CARCINOGEN.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION, RASH.

INHALATION: IRRITATION OF NOSE, THROAT, LUNGS. INGESTION:

GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, DIARRHEA.

Medical Cond Aggravated by Exposure:DERMATITIS AND RESPIRATORY TRACT IRRITATION.

=====
First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN:

WASH AREA WITH SOAP AND WATER. INHALATION: MOVE TO

FRESH AIR. IF SYMPTOMS PERSISTS GET MEDICAL ATTENTION. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING.

GET MEDICAL ATTENTION.

=====
Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:241F,116C

Extinguishing Media:FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:NONE ARE EXPECTED TO BE REQUIRED. IF THIS MATERIAL IS INVOLVED IN A

FIRE, NIOSH APPROVED SELF-CONTAINED RESPIRATORY EQUIPMENT SHOULD BE WORN.

Unusual Fire/Explosion Hazard:ALTHOUGH THIS MATERIAL IS NON-FLAMMABLE, VAPORS CAN COLLECT IN CLOSED CONTAINERS AND STORAGE VESSELS. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HIGH TEMP.

=====
Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. DIKE AND CONTAIN SPILL WITH INERT MATERIAL. TRANS

FER LIQUID AND DIKING MATERIAL TO CONTAINERS FOR
RECOVERY AND DISPOSAL. KEEP SPILLS OUT OF SEWERS AND OPEN WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. KEEP FROM
FREEZING.

Other Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT TAKE
INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

:WEAR MSHA/NIOSH APPROVED RESPIRATOR DURING AND
AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST
LEVELS ARE BELOW APPLICABLE LIMITS.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO CONTROL EXPOSURE LEVELS
BELOW AIRBORNE EXPOSURE LIMITS.

Protective Gloves:WEAR PROTECTIVE GLOVES.

Eye Protection:WEAR SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING WHENEVER POSSIBLE
TO PREVENT REPEATED OR EXTENDED EXPOSURE OF SKIN.

Work Hygienic Practices:W

ASH HANDS AFTER USING. REMOVE WET PAINT FROM
SKIN WITH WATER BEFORE IT DRIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Density: