

CONSOLIDATED MOTOR OIL CO INC -- LUBRICATING OIL, MIL-L-46017 -- 9150-00-402-4480  
===== Product Identification =====

Product ID:LUBRICATING OIL, MIL-L-46017  
MSDS Date:05/19/1993  
FSC:9150  
NIIN:00-402-4480  
MSDS Number: BQQLZ  
=== Responsible Party ===  
Company Name:CONSOLIDATED MOTOR OIL CO INC  
Address:1773 PINE AVE  
Box:427  
City:VINELAND  
State:NJ  
ZIP:08360-3442  
Country:US  
Info Phone Num:609-691-1066  
Emergency Phone Num:609-691-1066  
Preparer's Name:DGSC-SSH  
CAGE:9Z316  
=== Contractor Identification ===  
Company Name:CONSOLIDATED MOTOR OIL CO INC  
Address:1773 PINE AVE  
Box:427  
City:VINELAND  
State:NJ  
ZIP:08360-3442  
Country:US  
Phone:609-691-1066  
CAGE:9Z316

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL  
Other REC Limits:5 MG/M3 OIL MIST  
OSHA PEL:5 MG/M3 OIL MIST  
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:ADDITIVE PACKAGE CONTAINING ZINC, SULFUR, CA,

PHOSPHORUS  
AND NITROGEN.  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-INGESTION:LOW TOXICITY. MAY  
CAUSE GI TRACT IRRITATION. INHALATION:INHALATION OF  
MIST/VAPORS/FUMES MAY CAUSE RESPIRATORY TRACT IRRITATION. SMALL  
AMOUNT ASPIRATED INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS.

EYE:IRRITATION. SKIN:REPEATEDCONTACT MAY CAUSE IRRITATION.  
CHRONIC:DERMATITIS, OIL ACNE OR FOLLICULITIS.

Effects of Overexposure:EYE-IRRITATION. SKIN-DRYNESS & IRRITATION.  
INGESTION:DIARRHEA.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH EXISTING SKIN  
DISEASES MAY BE AT INCREASED RISK.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MINUTES BY HOLDING EYELID OPEN.  
IF IRRITATION OR REDNESS PERSIST CONSULT A PHYSICIAN.  
SKIN-REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. INGESTION: DO  
NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. INHALATION OF  
OIL MIST OR FUMES, REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF  
NEEDED. GET MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:410F,210C  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.  
Fire Fighting Procedures:DO NOT USE WATER STREAM DIRECTLY. USE WATER  
SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL.  
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER  
SUITABLE ABSORBENT TO SPILL AREA. DIKE AND KEEP PRODUCT OUT OF  
SEWERS & WATER COURSES. PUT WASTE IN A CONTAINER FOR PROPER  
DISPOSAL.  
Neutralizing Agent:NONE

===== Handl

ing and Storage =====

Handling and Storage Precautions:MINIMIZE SKIN CONTACT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STORE NEAR EXTREME HEAT OR OPEN FLAMES.

Other Precautions:DO NOT CREATE MIST. DO NOT INHALE MIST OR VAPORS PRODUCED AT HIGH TEMPERATURES. IF WORKING WITH MIST OR FUMES, NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPORS FILTER MUST BE WORN. WASH TH OROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. IF WORKING WITH MIST OR FUMES, USE NIOSH APPROVED SELF BREATHING RESPIRATOR WITH ORGANIC VAPOR FILTER.

Ventilation:NORMAL OR MECHANICAL

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON OR OTHER IMPERVIOUS CLOTHING.

Work Hygienic Practices:WASH HANDS AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORKING AREA.

Supplemental

Safety and Health

MSDS NOT AVAILABLE FROM MFR, 1985 CONTRACT. INFORMATION PRESENTED HEREIN IS ACCURATE AND RELIABLE TO THE BEST OF OUR KNOWLEDGE AND BELIEF BUT IS NOT GUARANTEED TO BE SO. IT IS THE USER'S RESPONSIBILIT Y TO TAKE ALL SAFETY PRECAUTIONS AS MAYBE NECESSARY. WE HEREBY DISCLAIM ALL LIABILITY WITH RESPECT TO IT'S USE.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>400F,>204C

Vapor Pres:1

Spec Gravity:0.86

Evaporation

Rate & Reference: