View NSN Online: https://aerobasegroup.de/nsn/5365-00-854-8007

R M ENGINEERED PRODUCTS, INC. -- RL-1688 GROMMET,43004383 -- 5365-00-854-8007

Product ID:RL-1688 GROMMET,43004383 MSDS Date:12/01/1992 FSC:5365 NIIN:00-854-8007 **MSDS Number: BQSGR** === Responsible Party === Company Name: R M ENGINEERED PRODUCTS, INC. Address:4854 O'HEAR AVENUE Box:5205 **City:NORTH CHARLESTON** State:SC ZIP:29406 Country:US Info Phone Num:803-744-6261 Emergency Phone Num:803-744-6261 CAGE:10009 === Contractor Identification === Company Name: KAMPI COMPONENTS CO., INC. Address:210 RT 13 Box:721 City:BRISTOL State:PA ZIP:19007-3517 Country:US Phone:215-736-2000 CAGE:7Z016 Company Name: R M ENGINEERED PRODUCTS, INC. Address:4854 O'HEAR AVENUE Box:City:NORTH CHARLESTON State:SC ZIP:29405 Country:US Phone:843-744-6261 CAGE:10009

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTE CS #:CI6478500 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:POLYTETRAFLUOROETHYLENE CAS:9002-84-0 Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:TLV FOR CHRYSOTILE ASBESTOS IS 2 F/CC. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE- NONE UNDER NORMAL CONDITIONS OF

USE. GRINDING, SANDING/MACHINING MAY PRODUCE NUISANCE PARTICULATES THAT CAN CAUSE IRRITATION OF EYES, SKIN, GI TRACT & RESPIRATORY PASSAGES. CHRONIC- LONG TERM E XPOSURE TO ASBESTOS CAN CAUSE IRREVERSIBLE ASBESTOSIS, LUNG DISEASE & LUNG CANCER. SMOKING GREATLY INCREASES THE RISKS.

Explanation of Carcinogenicity: ASBESTOS IS REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:NONE UNDER NORMAL CONDITIONS OF USE. HOWEVER, GRINDING, SANDING OR MACHINING MAY PRODUCE

NUISANCE PARTICULATES

THAT CAN CAUSE IRRITATION OF EYES, SKIN, GASTROINTESTINAL TRACT AND RESPIRATORY PASSAGES. MAY CAUSE NAUSEA, VOMITING AND DIARRHEA. Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN

DISORDERS SUCH AS DERMATITIS, RESPIRATORY PROBLEMS, LUNG DISEASE, BRONCHIAL HYPER-REACTIVITY OR ANY CONDITION THAT MAY BE AGGRAVATED BY NUISANCE DUST OR FIBERS.

First Aid:SEEK MEDICAL ATTE NTION IF SYMPTOMS DEVELOP. IN CASE OF EYE IRRITATION GENTLY RINSE WITH WATER FOR 15 MINUTES WHILE KEEPING EYELIDS OPEN. DO NOT RUB EYES. SKIN: WASH FREQUENTLY WITH SOAP AND WATER. INH ALATION: REMOVE TO FRESH AIR. INGESTION: UNLIKELY.

Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures: AVOID BREA

THING FUMES. WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:ASBESTOS FIBERS MAY BE RELEASED. FLUOROCARBON AND VARIOUS TOXIC FUMES MAY BE FORMED IN A FIRE.
======================================
 Spill Release Procedures:TREAT DUST AS FREE ASBESTOS. DO NOT DRY SWEEP OR USE COMPRESSED AIR. WET METHOD SHOULD BE USED FOR EXTRACTION OF DUST AND DEBRIS HIGH EFFICIENCY PARTICULATE APPARATUS (HEPA) VACUUMS SHOULD BE USED. A VOID WATER-POLLUTION. Neutralizing Agent:NOT RELEVANT
======================================
 Handling and Storage Precautions: AVOID CREATING DUST BY SANDING OR GRINDING THE PRODUCT. Other Precautions: USE IN WELL VENTILATED AREA. AVOID BREATHING DUST OR FIBERS. MINIMIZE CONTACT WITH SKIN. AVOID CONTACT WITH EYES. DO NOT RAISE DUST. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATIN G OR DRINKING. KEEP AWAY FROM REACH OF CHILDREN.
======================================
Respiratory Protection:USE NIOSH APPROVED HIGH EFFICIENCY FIBERS/FUMES RESPIRATOR WHEN AIRBORNE FIBER CONCENTRATIONS EXCEED THE PEL. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. NONE NORMALLY REQUIRED. Protective Gloves:LEATHER, COTTON OR RUBBER IF FRIABLE Eye Protection:DUST-RESISTANT SAFETY GOGGLES IF FRIABLE Other Protective Equipment:EYE WASH STATION AND SAFETY SH OWER, WORK
CLOTHING AND APRON AS REQUIRED. DO NOT WEAR CONTACT LENSES Work Hygienic Practices:DON'T TAKE PROTECTIVE GEAR/CLOTHING HOME IF EXPOSED TO DUST. DON'T SHAKE. DON'T EAT IN AREA WHERE ASBESTOS/DUST PRESENT.
Supplemental Safety and Health THE MANUFACTURER STATES THAT THIS PRODUCT IS CONSIDERED AN "ARTICLE" AS DEFINED BY OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 & THEREBY DOES NOT REQUIRED A MSDS. ALSO, THIS PRODUCT IS NOT CON SIDERED HAZARDOUS IN THE FORM

SHIPPED OR IN ITS END USE APPLICATION. HOWEVER, IT BECOMES HAZARDOUS IF MISHANDLED/MISUSED

HCC:T6 Decomp Temp:Decomp Text:500F,260C Solubility in Water:INSOLUBLE Appearance and Odor:OFF-WHITE BRAIDED MATERIAL - NO ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS AND OTHER INTERHALOGEN COMPOUNDS Stability Condition to Avoid:TEMPER ATURES ABOVE 250 C Hazardous Decomposition Products:ASBESTOS FIBERS MAY BE RELEASED. VARIOUS FLUOROCARBON FUMES, CARBON MONOXIDE AND CARBON DIOXIDE MAY BE FORMED.

Waste Disposal Methods: APPROVED LANDFILL. WASTE SHOULD BE CONTAINED IN IMPERMEABLE BAGS, LABELED AND DISPOSED IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This i

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.