

FISKE BROTHERS REFINING CO -- LUBRIPLATE 130-AA -- 9150-00-944-1025

=====
Product Identification
=====

Product ID:LUBRIPLATE 130-AA

MSDS Date:06/01/1989

FSC:9150

NIIN:00-944-1025

MSDS Number: BQSHD

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Pre

parer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENTS

=====
Hazards I

dentification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING EYES MAY CAUSE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS & FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A

LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:AMOUNTS ASPIRATED INTO LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/CLEAR WATER FOR AT LST 15 MINS/UNTIL IRRIT SUBSIDES. IF IRRIT PERSIST, CONSULT MD. SKIN:REMOVE ANY CONTAM

CLTHG & WASH W/SOAP & WARM WATER. IF INJECTED BY HIGH PRESS UNDER SKIN, REGARDLESE S OF APPEAR/ITS SIZE, CONT MD IMMED. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. INHAL:VAP PRESS IS VERY LOW & INHAL @ ROOM TEMP IS NOT A PROBLEM. IF OVERCOME BY VAP FROM HOT PROD, IMMED (SUPDAT)

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:400F,204C

Lower Limits:0.9%

Upper Limits:7%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . COOL EXPOSED CONTAINERS W/WATER.

Unusual Fire/Explosion Hazard:DO NOT STORE/MIX W/STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER W/SUITABLE PETROLEUM SOLVENT OR ADD ABSORBE

